



Merging control strategies of connected and autonomous vehicles at freeway on-ramps: a comprehensive review

Downloaded from: <https://research.chalmers.se>, 2025-12-05 00:13 UTC

Citation for the original published paper (version of record):

Zhu, J., Easa, S., Gao, K. (2022). Merging control strategies of connected and autonomous vehicles at freeway on-ramps: a comprehensive review. *Journal of Intelligent and Connected Vehicles*, 5(2): 99-111.
<http://dx.doi.org/10.1108/JICV-02-2022-0005>

N.B. When citing this work, cite the original published paper.

Merging control strategies of connected and autonomous vehicles at freeway on-ramps: a comprehensive review

Jie Zhu

Department of Architecture and Civil Engineering, Chalmers University of Technology, Gothenburg, Sweden

Said Easa

Department of Civil Engineering, Ryerson University, Toronto, Canada, and

Kun Gao

Department of Architecture and Civil Engineering, Chalmers University of Technology, Gothenburg, Sweden

Abstract

Purpose – On-ramp merging areas are typical bottlenecks in the freeway network since merging on-ramp vehicles may cause intensive disturbances on the mainline traffic flow and lead to various negative impacts on traffic efficiency and safety. The connected and autonomous vehicles (CAVs), with their capabilities of real-time communication and precise motion control, hold a great potential to facilitate ramp merging operation through enhanced coordination strategies. This paper aims to present a comprehensive review of the existing ramp merging strategies leveraging CAVs, focusing on the latest trends and developments in the research field.

Design/methodology/approach – The review comprehensively covers 44 papers recently published in leading transportation journals. Based on the application context, control strategies are categorized into three categories: merging into single-lane freeways with total CAVs, merging into single-lane freeways with mixed traffic flows and merging into multilane freeways.

Findings – Relevant literature is reviewed regarding the required technologies, control decision level, applied methods and impacts on traffic performance. More importantly, the authors identify the existing research gaps and provide insightful discussions on the potential and promising directions for future research based on the review, which facilitates further advancement in this research topic.

Originality/value – Many strategies based on the communication and automation capabilities of CAVs have been developed over the past decades, devoted to facilitating the merging/lane-changing maneuvers at freeway on-ramps. Despite the significant progress made, an up-to-date review covering these latest developments is missing to the authors' best knowledge. This paper conducts a thorough review of the cooperation/coordination strategies that facilitate freeway on-ramp merging using CAVs, focusing on the latest developments in this field. Based on the review, the authors identify the existing research gaps in CAV ramp merging and discuss the potential and promising future research directions to address the gaps.

Keywords Ramp merging, Connected and autonomous vehicles, Vehicle coordination, Mixed traffic, Multilane freeway

Paper type Literature review

1. Introduction

On-ramp merging is critical for freeway traffic operation since the cut-in maneuvers of ramp vehicles impose frequent disturbances on the mainline traffic flow and cause various problems. These include traffic oscillations, increased fuel usage and emissions, safety concerns and recurrent traffic congestions (Cassidy and Bertini, 1999; Mergia *et al.*, 2013; Srivastava and Geroliminis, 2013; Han and Ahn, 2018; Wang *et al.*, 2019; Larsson *et al.*, 2021; Ali *et al.*, 2021; Zhang and Yang, 2021). However, with vehicle communication and autonomous driving technologies, new possibilities exist to prevent or mitigate such adverse traffic effects in the ramp

merging areas. Traditional traffic management approaches such as ramp metering (Papageorgiou *et al.*, 1991; Papageorgiou *et al.*, 1997; Ahn *et al.*, 2007; Papamichail *et al.*, 2010), variable speed limits/mainline metering (Carlson *et al.*, 2010; Jin *et al.*, 2017; Zhang *et al.*, 2017; Peng *et al.*, 2021; Lu and Liu, 2021; Chen *et al.*, 2021c) and hard shoulder running

The current issue and full text archive of this journal is available on Emerald Insight at: <https://www.emerald.com/insight/2399-9802.htm>



Journal of Intelligent and Connected Vehicles
5/2 (2022) 99–111
Emerald Publishing Limited [ISSN 2399-9802]
[DOI 10.1108/JICV-02-2022-0005]

© Jie Zhu, Said Easa and Kun Gao. Published in *Journal of Intelligent and Connected Vehicles*. Published by Emerald Publishing Limited. This article is published under the Creative Commons Attribution (CC BY 4.0) licence. Anyone may reproduce, distribute, translate and create derivative works of this article (for both commercial and non-commercial purposes), subject to full attribution to the original publication and authors. The full terms of this licence may be seen at <http://creativecommons.org/licences/by/4.0/legalcode>

The authors are grateful to VINNOVA (ICV-Safe, 2019–03418), Area of Advance Transport and AI Center (CHAIR) at the Chalmers University of Technology for funding this research.

Received 9 February 2022

Revised 25 February 2022

Accepted 28 February 2022

(Haj-Salem *et al.*, 2014; Li *et al.*, 2014). Unfortunately, these approaches can only control the traffic at an aggregated level. The emerging connected and autonomous vehicles (CAV) provide an opportunity to regulate the behaviors of individual vehicles and facilitate advanced cooperation and coordination in the on-ramp merging areas.

Many strategies based on the communication and automation capabilities of CAVs have been developed over the past decades, devoted to facilitating the merging/lane-changing maneuvers at freeway on-ramps. Though sharing the common objective of improved ramp merging operation, the existing strategies present substantial differences in many aspects, for example, the required vehicle technologies (connected, autonomous or connected and autonomous), the required level of automation (fully automated, partially automated or driver-assisted), the direction of control (longitudinal, lateral or both), the method of control (optimal control, feedback control or others) and the type of control (centralized or decentralized). The prior efforts have been reviewed by Scarinci and Heydecker (2014), Bevly *et al.* (2016) and Rios-Torres and Malikopoulos (2017b). As the initial attempts to coordinate CAVs at on-ramp merging, the prior strategies mainly focus on interactions between a few individual vehicles. Their benefits are only demonstrated in simple use cases. Further, assumptions on traffic compositions and freeway layouts are usually simplified in these studies. In recent years, significant advances have been made in CAV ramp merging. These include developing strategies targeting improvements at the continuous traffic flow level, developing strategies for the traffic conditions where CAVs and human-driven vehicles (HDV) coexist and developing strategies for multilane freeways where the free lane changes between mainline lanes may affect the merging traffic. Despite the significant progress made, an up-to-date review covering these latest developments is missing to the authors' best knowledge.

This paper conducts a thorough review of the cooperation/coordination strategies that facilitate freeway on-ramp merging using CAVs, focusing on the latest developments in this field. Based on the review, we identify the existing research gaps in CAV ramp merging and discuss the potential and promising future research directions to address the gaps. The review comprehensively covers 44 papers recently published in leading transportation journals[1]. Based on the application contexts, the reviewed works are categorized into three groups of strategies: one-lane freeways with a total CAV penetration rate, one-lane freeways with mixed CAV-HDV traffic conditions and strategies for multilane freeways. We categorize relevant literature based on two criteria: one-lane or multilane in the mainline and CAV-only or mixed traffic flow. The number of lanes of mainline in merging areas determines whether vehicles in mainline can make lane-changing maneuvers and thus significantly influence merging control strategies and problem complexity. CAV-only or mixed traffic determines whether human drivers who cannot be controlled are involved and thus affect control strategy notably. Therefore, control strategies vary pretty remarkably with the two factors, which are the criteria used to categorize relevant literature. The number of reviewed papers for each category is summarized in Table 1.

Note that not all the reviewed studies assume the same level of CAV capabilities. For example, some strategies require

connected vehicles (CV) with on-board driver advisory systems, and some apply to autonomous vehicles (AV) with high-resolution sensors. However, these strategies are essentially the same as the strategies requiring complete CAV capabilities. For example, the strategies that involve only CV are usually achieved by assuming that the human drivers will strictly follow the recommendations from the advisory system (i.e. the human drivers will perform the same level of vehicle control as AV). Therefore, such strategies can be directly transferred to the CAV operation for even better performance. In this sense, we include these studies in the review. Detailed characteristics of the strategies, including vehicle capabilities, penetration level, freeway layout, control decisions and primary analysis method, are presented in Table 2.

The remainder of the paper is structured as follows. Section 2 reviews the primary strategies for single-lane freeways with a total CAV penetration rate. Section 3 presents the strategies for single-lane freeways with mixed traffic, and Section 4 summarizes the strategies for multilane freeway configurations. Section 5 presents a critical discussion on existing research gaps and future research directions. Finally, Section 6 presents the concluding remarks.

2. Merging control for single-lane freeways with connected and autonomous vehicles-only

The CAV's ability to perform cooperative and coordinative merging is endowed by emerging vehicle communication and automation technologies. The communication technologies allow for detailed and timely information exchange among road users, traffic infrastructures and control centers using dedicated short-range radio communications and cellular networks. As a result, the maneuvers of vehicles can be planned via real-time negotiations among traffic participants. Further, autonomous driving systems in vehicles can execute the planned activities can be executed in a stable and timely manner, as they are less prone to delays and errors in the processes of recognition, decision-making and performance. Depending on the level of control, the existing CAV-enabled merging strategies can be divided into operational control and tactical control. The operational control layer determines lower-level actions of vehicles, such as step-by-step acceleration and deceleration. In contrast, the tactical control layer addresses the upper-level decisions, such as merging sequence and gap. This section reviews the strategies for the context of the single-lane freeways and the total CAV penetration rate (demonstrated in Figure 1) at both levels. In reality, there are generally multiple lanes in the mainline. Therefore, the controls for single-lane freeways assume no lane-changing behaviors in the most-outer lane.

2.1 Lower-level control

At the lower level, the actions of relevant vehicles can be planned to enhance the traffic performance at on-ramp merging. A typical approach to solve the mainline-ramp conflict at merging is to use the concept of "virtual vehicle/virtual platooning," namely, mapping the mainline and ramp vehicles to each other's lane so that the merging problem is transformed into a virtual car-following problem. By following the virtual leader, instead of the physical leader, the vehicles adjust their longitudinal positions in advance for smooth and

Table 1 Number of papers reviewed for different ramp merging categories

Category no.	Vehicle technology	Mainline	No. of reviewed papers	Primary methods
1	CAV-only	One-lane	24	– Optimization – Machine learning – Traffic modeling – Feedback control – Virtual vehicle
2	Mixed	One-lane	10	– Generic algorithm – Optimization – Machine learning – Traffic modeling – Car following – Virtual
3	CAV-only or Mixed	Multilane	10	– Optimization – Machine learning – Feedback control – Fuzzy control – Game theory

safe merging. Milanés *et al.* (2010) develop a fuzzy controller for vehicle throttle and brake control, which allows the vehicles to maintain a reference distance to their virtual leaders. The controller is validated in real-world experiments, where a test vehicle successfully merges in between the other two vehicles. Several subsequent studies use a similar idea of the virtual platoon for collision-free merging operations (Wang *et al.*, 2013; Chen *et al.*, 2021b; Hu *et al.*, 2021; Liao *et al.*, 2021; Mu *et al.*, 2021). Though these approaches facilitate smooth and safe merging, their benefits in merging efficiency are somewhat limited, as the solutions are more intuitive than systematically optimal.

Instead of using intuitive control strategies in the aforementioned literature, other studies were committed to improving CAV merging trajectories under an optimization framework. The key differences of this stream of studies are that they formulated optimization control models and corresponding solvers to obtain the control variables via optimization rather than predefined rules. The optimization models in different studies target different objectives favoring traffic efficiency, energy use and passenger comfort while subject to vehicle dynamics, safety requirements and technical constraints. For example, Cao *et al.* (2015) abstracted a ramp merging area as lines in a two-dimensional rectangular coordinate system to describe the interaction between a ramp merging vehicle and its mainline follower. The motions of the vehicles were jointly planned by minimizing a penalty function consisting of acceleration, speed deviation, ramp vehicle's lateral position and distance between the two conflicting vehicles. The algorithm was implemented in a model predictive control (MPC) scheme and realized cooperative and collision-free merging behaviors in the simulation. Similarly, Zhou *et al.* (2019a) formulated cooperation between a pair of the ramp and mainline vehicles as two optimal trajectory planning problems related to each other. The algorithm considered explicit bounds on vehicle acceleration and allowed for a flexible choice of merging location. In the optimization framework, the optimal control of facilitated cars in the mainline is given by:

$$\min_{u(t)} \int_0^{t_f} \frac{1}{2} [u(t)^2 + \lambda] dt \quad (1)$$

subject to:

$$\begin{aligned} \dot{\mathbf{x}}(t) &= \begin{bmatrix} \dot{x}(t) \\ \dot{v}(t) \end{bmatrix} = \begin{bmatrix} v(t) \\ u(t) \end{bmatrix} \\ a_{\min} &< u(t) < a_{\max} \\ x(0) &= x_0, v(0) = v_0 \\ x(t_f) &= x_e, v(t_f) = v_e \end{aligned} \quad (2)$$

where t_f is the period of the merging process; $x(t)$ and $v(t)$ are state variables representing the distance and speed of the facilitating vehicle; x_0 and v_0 are the initial states when merging control starts, x_e and v_e are the anticipated and final states after controls; and λ is a constant term for penalizing the duration of the merging process. Meanwhile, the optimal control problem for the on-ramp merging vehicle is formulated as:

$$\min_{u(t)} \int_0^{t_f} \frac{1}{2} [u(t)^2] dt + \frac{1}{2} \lambda_1 [x(t_f) - x_e^m]^2 + \frac{1}{2} \lambda_2 [v(t_f) - v_e^m]^2 \quad (3)$$

subject to:

$$\begin{aligned} \dot{\mathbf{x}}(t) &= \begin{bmatrix} \dot{x}(t) \\ \dot{v}(t) \end{bmatrix} = \begin{bmatrix} v(t) \\ u(t) \end{bmatrix} \\ a_{\min} &< u(t) < a_{\max} \\ x(0) &= x_0^m, v(0) = v_0^m \\ x(t_f) &= x_e^m, v(t_f) = v_e^m \end{aligned} \quad (4)$$


where x_e^m and v_e^m are desired location and speed of merging vehicles after controls. λ_1 and λ_2 are two constant weighting factors to penalize deviation from desired location and speed.

Table 2 Characteristics of the reviewed ramp merging strategies

Category	Reference	Veh. tech.	Penet. level	Freeway layout	Control decision Upper level	Lower level	Primary method
1. CAV-only and one-lane	Chen <i>et al.</i> (2021b)	CAV	Total	One-lane	– b	Trajectory	Feedback control
	Hu <i>et al.</i> (2021)	CAV	Total	One-lane	–	Trajectory	Feedback control
	Liao <i>et al.</i> (2021)	CV	Total	One-lane	–	Trajectory	Feedback control
	Sonbolestan <i>et al.</i> (2021)	CAV	Total	One-lane	–	Trajectory	Optimization
	Xu and Shen (2021)	CAV	Total	One-lane	–	Trajectory	Optimization
	Chen <i>et al.</i> (2020)	CAV	Total	One-lane	–	Trajectory	Optimization
	Ding <i>et al.</i> (2020)	CAV	Total	One-lane	Merging gap choice	Trajectory	Optimization
	Fukuyama (2020)	CAV	Total	One-lane	Merging sequence	Trajectory	Optimization
	Jing <i>et al.</i> (2019)	CAV	Total	One-lane	–	Trajectory	game theory
	Nishi <i>et al.</i> (2019)	CAV	Total	One-lane	Merging sequence	Trajectory	Optimization
	Pei <i>et al.</i> (2019)	AV	Total	One-lane	Merging gap choice	Trajectory	Machine learning
	Xu <i>et al.</i> (2019a)	CAV	Total	One-lane	Merging sequence	–	Optimization
	Xu <i>et al.</i> (2019b)	CAV	Total	One-lane	Merging sequence	–	Optimization
	Zhou <i>et al.</i> (2019a)	CAV	Total	One-lane	Merging sequence	–	Optimization
	Zhou <i>et al.</i> (2019b)	CAV	Total	One-lane	Merging sequence	–	Optimization
	Letter and Eleftheriadou (2017)	CAV	Total	One-lane	–	Trajectory	Generic algorithm
	Rios-Torres and Malikopoulos (2017a)	CAV	Total	One-lane	–	Trajectory	Optimization
	Scarinci <i>et al.</i> (2017)	CAV	Total	One-lane	–	Trajectory	Optimization
	Ward <i>et al.</i> (2017)	CAV	Total	One-lane	–	Trajectory	Optimization
	Xie <i>et al.</i> (2017)	AV	Total	One-lane	Periodic gap	–	Traffic modeling
	Ntousakis <i>et al.</i> (2016)	CAV	Total	One-lane	–	Trajectory	Optimization
	Cao <i>et al.</i> (2015)	CV	Total	One-lane	–	Trajectory	Optimization
	Wang <i>et al.</i> (2013)	CAV	Total	One-lane	–	Trajectory	Optimization
	Chen <i>et al.</i> (2021a)	CAV	Mixed	One-lane	Periodic gap, batch merge	–	Virtual vehicle
2. Mixed and one-lane	Rios-Torres and Malikopoulos (2018)	CAV	Mixed	One-lane	–	Trajectory	Traffic modeling
	Kherroubi <i>et al.</i> (2021)	CAV	Mixed	One-lane	–	Trajectory	Machine learning
	Mu <i>et al.</i> (2021)	CAV	Mixed	One-lane	–	Trajectory	Optimization
	Okuda <i>et al.</i> (2021)	AV	Mixed	One-lane	–	Trajectory	Optimization
	Karimi <i>et al.</i> (2020)	CAV	Mixed	One-lane	–	Trajectory	Optimization
	Omidvar <i>et al.</i> (2020)	CAV	Mixed	One-lane	–	Trajectory	Optimization
	Sun <i>et al.</i> (2020)	CAV	Mixed	One-lane	Merging gap choice	Trajectory	Optimization
	Ding <i>et al.</i> (2019)	CAV	Mixed	One-lane	Merging sequence	Trajectory	Optimization
	Ito <i>et al.</i> (2019)	CAV	Mixed	One-lane	–	Trajectory	Optimization
	Zhou <i>et al.</i> (2017)	AV	Mixed	One-lane	–	Trajectory	Car-following
3. CAV-only or mixed multilane	Gao <i>et al.</i> (2021)	CAV	Mixed	Multilane	–	Trajectory	Optimization
	Hang <i>et al.</i> (2021)	CAV	Total	Multilane	–	Trajectory	Optimization
	Pan <i>et al.</i> (2021)	CAV	Mixed	Multilane	Ramp inflow	LC, trajectory	Game theory
	Liu <i>et al.</i> (2021)	CAV	Total	Multilane	–	LC, speed	Optimization
	Williams <i>et al.</i> (2021)	CAV	Mixed	Multilane	–	Trajectory	Machine learning
	Guo <i>et al.</i> (2020)	CAV	Mixed	Multilane	–	Trajectory	Car-following
	Karbalaei <i>et al.</i> (2020)	CAV	Total	Multilane	–	LC, speed	Machine learning
	Tajdari <i>et al.</i> (2020)	CV	Mixed	Multilane	LC/ramp flows	–	Optimization
	Hu and Sun (2019)	CAV	Total	Multilane	–	–	Feedback control
	Milanés <i>et al.</i> (2010)	CV	Total	Multilane	–	Trajectory	Optimization
						Trajectory	Fuzzy control

Notes: ^aLC: lane change; ^bnot applicable

Figure 1 Merging scenario of single-lane freeways with a total CAV penetration rate



The optimization was recursive to address the external disturbances introduced by the leading vehicle, and validated through numerical experiments for improving merging smoothness and computation cost. Similarly, [Xu and Shen \(2021\)](#) shed light on the merging of hybrid electric vehicles (HEV). They jointly decided the speed and torque distribution between the engine and motor of an automated HEV at ramp merging for minimal travel time and energy cost. In the branch of centralized merging control, the merging efficiency of relevant vehicles can be jointly improved. Moreover, [Liao et al. \(2021\)](#) designed a cooperative system for CV based on vehicle-to-cloud (V2C) communication. Vehicles uploaded real-time status to the cloud server to determine the advisory speed for a ramp vehicle to merge between two mainline vehicles.

However, merely considering one vehicle in trajectory planning will neglect the impacts of controls of one vehicle on other vehicles in the traffic flow, which may lead to suboptimal. To overall, such a shortcoming, the control scope was extended from a single pair of vehicles to a series of vehicles in the communication range. [Ntousakis et al. \(2016\)](#) assumed the existence of a predetermined merging sequence of relevant vehicles, and the vehicles collected information from their physical and putative leaders to plan their optimal trajectories. The study considered various cost functions, including vehicle acceleration, jerk and the first derivative of the jerk. The results showed its superiority to a typical adaptive cruise control controller in terms of engine effort and passenger comfort. [Rios-Torres and Malikopoulos \(2017a\)](#) organized the vehicles in the first-in-first-out order and established an optimal framework to minimize the total fuel consumption of all vehicles in the control area. Merging collisions were avoided by regulating only one vehicle that may cross the merging zone. A closed-form solution was analytically derived using Hamiltonian analysis, and simulations were carried out to examine the benefits of the merging algorithm in smoothing vehicle trajectory and reducing fuel consumption. Later, the idea to reduce fuel consumption via trajectory planning was further adopted by [Sonbolestan et al. \(2021\)](#). The authors determined the optimal merging position of a ramp vehicle for the mainline. The strategy was tested in a simulation with field traffic data as inputs. [Letter and Elefteriadou \(2017\)](#) developed an optimization-based strategy to maximize the average speed of vehicles in the merging area. The algorithm first determined a merging sequence based on the estimated arrival times of vehicles and then constrained motions of each vehicle on the trajectory of its leading vehicle. The strategy worked even in oversaturated conditions to increase merging throughput, efficiency and comfort. Similarly, the strategy in [Xie et al. \(2017\)](#) targeted maximizing the total speed of all vehicles over a specific decision interval while ensuring safety distances between successive vehicles in all lanes. The developed

strategy outperformed a no-control case and a gradual speed limit strategy in terms of throughput, vehicle speed and delay.

Besides the abovementioned methods, some other approaches have been developed for motion decisions at CAV ramp merging. In [Ward et al. \(2017\)](#), a set of candidate trajectories were evaluated to select the optimal one based on a cost function incorporating merging progress, comfort and risk. The evaluation of candidate trajectories considers the responsive motions of surrounding vehicles predicted by a probabilistic intelligent driver model (IDM). [Fukuyama \(2020\)](#) used a two-player dynamic game approach to interpret the interactions between a competing pair of vehicles. Under this approach, each vehicle made trajectory decisions to maximize its driving utility while considering the potential actions/responses of the competing vehicle. Recently, feedback and feedforward methods have been applied in real-time CAV motion control. For example, [Chen et al. \(2021b\)](#) designed a motion controller that used the speed difference and spacing error as the feedback components and the acceleration of predecessors as the feedforward information to produce longitudinal motion commands. The string stability for the proposed controller was analytically proven. In [Hu et al. \(2021\)](#), a motion controller was designed to handle the nonlinearity and time-varying uncertainties in vehicle dynamics. The controller took the spacing error as the control object. Its effectiveness was assessed under critical situations with speed variations of the surrounding vehicles and simultaneous merging of multiple ramp vehicles.

2.2 Upper-level control

As reviewed in Section 2.1, many lower-level motion planning strategies require a merging sequence as input. However, the merging sequence is determined intuitively based on relatively simple rules, such as first-in-first-out, virtual vehicle mapping and estimated arrival time. This leaves a chance to further improve the merging coordination through more efficient designs of the merging sequence.

Some recent studies shed light on the problem of merging sequence planning. For example, [Xu et al. \(2019b\)](#) used a genetic algorithm to solve the choice of a merging sequence. In addition, the utilities of candidate sequences were assessed by a fitness function combining the travel time of mainline vehicles and the number of ramp vehicles allowed to merge as follows:

$$\max F = w_1 f_{\text{mainline}} + w_2 f_{\text{merging}} + g_1 e_v + g_2 e_s \quad (5)$$

subject to:

$$\begin{aligned} 0 &\leq w_1 \leq 1 \\ 0 &\leq w_2 \leq 1 \\ w_1 + w_2 &= 1 \\ a_{\min} &\leq a_j \leq a_{\max} \end{aligned} \quad (6)$$

where f_{mainline} and f_{merging} are the utility functions for vehicles in the mainline and ramps, which are related to the travel time and number of merged vehicles; w_1 and w_2 are constant weights; e_v is the error of vehicle speeds after merging; e_s is the error of spacings between vehicles after merging; and g_1 and g_2 are penalty factors. A genetic algorithm is used to solve the optimization. The algorithm encoded the merging sequences in a binary


representation and samples candidate sequences through selection, crossover and mutation, as illustrated in Figure 2. After a certain number of generations, the merging sequence with the maximal fitness value was chosen. In Xu *et al.* (2019a), vehicles whose inter-vehicle distances were lower than a predefined threshold were grouped, and the merging order of vehicles within a group remained unchanged. Then, the groups were sequenced by enumerating all possible orders to select the one with minimal total passing time and delay. The proposed strategy could find near-optimal solutions with less computation time and a good tradeoff between computation efficiency and traffic performance. Similarly, Pei *et al.* (2019) developed a strategy to improve the computation efficiency of searching for the optimal merging sequence at the prerequisite of maintaining the optimality of the result. By stipulating that vehicles on the same road follow a first-in-first-out order, the strategy assigned the right of way between the two links (mainline/ramp) instead of among individual vehicles so that the complexity of the sequencing problem was substantially reduced.

Moreover, several recent studies have integrated the choice of a merging sequence with the planning of vehicle trajectories. For example, Ding *et al.* (2020) designed a series of rules to adjust the merging order of vehicles and then planned the motion of each vehicle accordingly. Based on the idea that the headway between vehicles from different roads is usually larger than that from the same road, the proposed rules allowed vehicles from the same road to pass the merging area together to reduce the switch of the right of way. Jing *et al.* (2019) developed an optimization model for integrated merging sequence and trajectory decisions. The model objective consisted of a strategy cost related to merging sequence and an action cost determined by vehicle accelerations

and jerks. Alternative to a decision on the merging sequence, Chen *et al.* (2020) determined a merging gap for each ramp vehicle. The strategy was composed of a tactical layer and an operational layer. The tactical layer used a second-order dynamics model to estimate the trajectory costs for different gaps and select the gap with the least cost for the vehicle. The operational layer further optimized the trajectory with a third-order dynamics model. Similarly, Nishi *et al.* (2019) made a joint decision on the merging gap and its trajectory for each ramp vehicle. The strategy chose the policy with the lowest cost based on the state value function learned from field data using a passive actor-critic method.

The above CAV ramp merging strategies mainly focused on controlling individual vehicles and benefits at the local and microscopic levels. Through an aggregated control of the two streams of traffic at on-ramp merging, improvements in the overall traffic flow performance can be achieved. An example of such an aggregated control system was introduced in Scarinci *et al.* (2015) and Scarinci *et al.* (2017). Under the control strategy, the mainline traffic was periodically compacted to create large gaps, and the ramp vehicles were released into the gaps through ramp metering signals. However, this strategy stipulated that the release of ramp vehicles entirely depended on the mainline conditions, so the efficiency of ramp traffic was not actively considered. The strategy was established based on the macroscopic traffic flow theories, with explicit consideration of the dynamics of gap formation. The validation indicated that the proposed strategy was compatible with real-world implementation and could reduce the occurrence of congestions and the number of late-merging vehicles.

Figure 2 Merging sequence representation and flowchart of used genetic algorithm



Source: Xu *et al.* (2019b)

3. Merging control for single-lane freeways with mixed traffic

It is widely predicted that before the complete launch of CAVs, there will be a long period when the CAVs and HDVs share the public roads. This will lead to significant challenges in the ramp merging control of CAVs, as the uncontrollability of HDVs will introduce various uncertainties into traffic operation. Therefore, recent research efforts are applied to the design of CAV control strategies in the presence of HDVs, as displayed in Figure 3. This section will review control strategies in the contexts of single-lane freeways with both CAVs and HDVs.


A typical control problem for the mixed traffic is to guide a CAV from the on-ramp to merge into the mainline traffic with HDVs, where the actions of HDVs should be predicted and explicitly considered in the motion plan of CAVs. To resolve this issue, [Kherroubi et al. \(2021\)](#) trained a probabilistic classifier using artificial neural networks and field data to predict the passing intentions of human drivers. The prediction further served as an input of a reinforcement learning agent to control the longitudinal acceleration of a ramp CAV. The simulation showed the control's ability to reduce the number of vehicle conflicts and stops at ramp merging. In [Okuda et al. \(2021\)](#), a logistic regression model was developed to estimate the decisions of the mainline human drivers (expressed as the probability to accept a vehicle to merge in front of it). Based on these decisions, a merging strategy was proposed to maximize the acceptance probability of the mainline human drivers by proactively adjusting the speed of the merging CAV. The optimization formulation is given by:

$$\min \sum_{k=1}^K \sum_{c=1}^N S^c(k|t) \quad (7)$$

subject to:

$$\begin{aligned} S^c(t) &= -\sum_{s=1}^3 P(X_{SOD}(t) = s | \phi(t)) \times \log_2 P(X_{SOD}(t) = s | \phi(t)) \\ P(X_{SOD}(t) = s | \phi(t)) &= \begin{cases} \frac{\exp(\eta_s^T \phi(t))}{1 + \exp(\eta_1^T \phi(t)) + \exp(\eta_2^T \phi(t))} & \text{if } s = 1 \text{ or } 2 \\ 1 - P_1(\phi(t)) - P_2(\phi(t)), & \text{if } s = 3 \end{cases} \\ \mathbf{A}^E(t) &= (d^{M,E}(t), v^{M,E}(t), a^{M,E}(t))^T \\ \mathbf{E}^E(t) &= (d^{L,E}(t), v^{\gamma,E}(t), L_w)^T \\ \phi(t) &= (\mathbf{1}, \mathbf{A}^E(t)^T, \mathbf{E}^E(t)^T)^T \\ s = 1 &: \text{accept} \\ s = 2 &: \text{rejected} \\ s = 3 &: \text{undecided} \end{aligned} \quad (8)$$

Figure 3 Merging scenario of single-lane freeways with mixed traffic



where t is the current time and k is the time index in the prediction horizon; K is the total number of steps in the prediction horizon; $d^{M,E}$, $v^{M,E}$ and $a^{M,E}$ are distance, relative speed and relative acceleration between the following vehicle in the mainline and merging vehicle in ramps, respectively; $d^{L,E}(t)$ is the distance between the leading vehicle in the mainline and the merging vehicle and $v^{\gamma,E}(t)$ is the distance of the merging vehicle to the end of the acceleration lane. The control strategy was executed in a MPC scheme. In contrast to the control of ramp merging CAVs, [Zhou et al. \(2017\)](#) focused on the control of CAVs on the main road. The authors used the IDM to capture the adaptive and cooperative behaviors of the mainline CAVs. Further, they showed through an illustrative case study that the increase in CAV penetration rate could reduce the total travel time and smooth traffic oscillations at on-ramp merging.

Moreover, some research was devoted to facilitating ramp merging through simultaneous control of the mainline and ramp vehicles. The earlier work by [Zhou et al. \(2019a\)](#) jointly planned motions of a ramp merging vehicle and a mainline facilitating vehicle. Subsequently, [Zhou et al. \(2019b\)](#) further introduced a lower bound on the cooperative speed of the facilitating vehicle to restrain the adverse impacts on the upstream traffic and avoid undesired speed-drops on the main road. The improved strategy was tested under mixed flow conditions. The results showed the strategy's ability to reduce the risk of rear-end collisions and mitigate speed variations of the mainline traffic flow. [Karimi et al. \(2020\)](#) divided the merging situations into six categories depending on the combinations of CAVs and HDVs in a merging triplet (i.e. a merging vehicle and its putative leader and follower in the target lane). They also developed for each category a cooperative strategy that checked the desired speed and inter-vehicle distance at a series of set-points. Numerical studies showed that such a strategy could achieve smooth and cooperative merging.

The above strategies for mixed traffic flow focused on the interaction between a single ramp vehicle and its direct neighbors on the main road. However, they neglected the influence on the surrounding traffic. By jointly planning the motions of multiple vehicles under an optimization framework, the overall traffic performance in the merging area can be improved. [Mu et al. \(2021\)](#) developed a trajectory planning method that first forms multiple mainline and ramp vehicles into a virtual platoon. Then, they planned their motions to maximize the average vehicle distance traveled over a specific planning period. The strategy was extended to the mixed CAV-HDV conditions in two steps:

- 1 dividing the mixed string of vehicles into blocks containing a leading CAV and several following HDVs; and
- 2 considering each block as a whole trajectory planning problem.

[Ito et al. \(2019\)](#) designed a merging planning system where a global controller collects CAV information and estimates the states of HDVs. The state information was encoded and broadcast to all road users in the merging areas so that the local controllers on CAVs could use the information to plan their trajectories. [Omidvar et al. \(2020\)](#) extended the merging strategy in [Letter and Eleftheriadou \(2017\)](#) for the mixed traffic

flow. The model accounted for deviations between the predicted and actual behaviors of HDV through a real-time correction mechanism yet oversimplified HDV driving patterns. Sun *et al.* (2020) integrated the choice of merging gap and the design of vehicle trajectories into an optimization problem. The problem assumed different driving rules for CAVs and HDVs and considered the benefits of a series of upstream vehicles on the main road. Ding *et al.* (2019) applied their previous strategy (Ding *et al.*, 2020) to the mixed CAV-HDV condition. They discussed the impacts of CAV penetration on throughput, traffic efficiency, fuel use and emission. Similarly, Rios-Torres and Malikopoulos (2018) applied the motion planner developed in Rios-Torres and Malikopoulos (2017a) to an environment where CAV and HDV coexisted to investigate how the increasing percentage of CAVs may influence the energy use at on-ramp merging. Nevertheless, these studies (Rios-Torres and Malikopoulos, 2018; Ding *et al.*, 2019) were more focused on assessing the impacts of CAV penetration under the existing control framework rather than designing a specific CAV control strategy for the mixed traffic conditions.

At the traffic flow level, Chen *et al.* (2021a) adopted the idea of periodic gap creation and combined it with a batch merging strategy to close the extra time gaps induced by the lane-changing maneuvers of on-ramp vehicles. It was demonstrated in theory that the proposed system could reduce unused roadway capacity and increase merging throughput, but no numerical/simulation experiment was carried out.

4. Merging control for multilane freeways

The above-reviewed strategies consider a simple freeway layout with one-lane on each road and ignore the lane-changing behaviors between the mainline lanes. Nevertheless, the single-lane freeway layout is less common in practice. This section reviews the CAV ramp merging strategies designed for the more realistic multilane freeway configurations, as demonstrated in Figure 4. With the presence of multiple lanes on the main road, the lane-changing decisions of mainline vehicles may influence the merging opportunities of ramp

vehicles and introduce more uncertainties in the ramp merging cooperation, presenting significant challenges for CAV control.

A prior effort to address such a challenge is Marinescu *et al.* (2012). The authors designed a hybrid system combining centralized and decentralized control to account for the negotiations between the mainline and ramp vehicles. The system divided the space on a multilane freeway into moving slots and assigned slots to vehicles for easy merging. It was stipulated that the mainline vehicles tend to move into the free slots in their front left to use the space in the inner lanes so that more slots were released for the merging of on-ramp vehicles. Following similar ideas, subsequent studies proposed various solutions to release the space in the outermost lane via proactive controls of CAVs. For example, Karbalaieali *et al.* (2020) considered a two-lane freeway and chose from various combinations of alternative actions (i.e. speeding up, slowing down or changing lanes) the one that minimized the total travel time of a ramp vehicle and its direct mainline competitors. Though presenting improvements in traffic efficiency, the proposed strategy used a discrete decision space, leaving room for more sophisticated action control. Hang *et al.* (2021) interpreted the merging process as a coalitional game involving a ramp vehicle and the mainline vehicles directly influenced by it. In the game, each vehicle decided whether it would behave cooperatively (join a coalition) or independently (leave a coalition) based on its individualized orientation toward efficiency, safety and comfort. The lane-changing decisions and longitudinal vehicle trajectories in each coalition were optimized for the maximal benefits of the coalition. Karbalaieali *et al.* (2020) and Hang *et al.* (2021) considered one ramp vehicle only once, making the strategies less effective when the on-ramp vehicles arrived frequently. To accommodate the merging of multiple ramp vehicles, Hu and Sun (2019) extended the trajectory optimization strategy of Letter and Elefteriadou (2017) to implement a multilane layout. Their extensive strategy designed a cooperative lane-changing zone upstream of the trajectory control zone. A part of mainline vehicles in the outer lane was allocated to the inner lane to balance the after-merging flow between mainline lanes. The merging trajectory was optimized to maximize the subject vehicle's velocity during the optimization process, as follows:


$$\min \left(-\sum_{t=1}^{T_{CM}} v_t \right) \quad (9)$$

subject to:

$$\begin{aligned} v_t &\in [0, v_{\max}^{CM}] \\ a_t &\in [a_{\min}^{CM}, p \cdot v_t + q] \\ |j_t| &\leq j_{\max}^{CM} \quad \forall t \in \{2, 3, \dots, T_{CM}\} \\ X_t - x_t &\geq v_t g_{\min}^{CM} \\ X_t - x_t &\geq d_{\min} \\ x_t - x_{t-1} &= v_{t-1} \Delta t^{CM} \\ v_t - v_{t-1} &= a_{t-1} \Delta t^{CM} \end{aligned} \quad (10)$$

where t is time step index; x_t and X_t are the positions of the subject vehicle and conflicting vehicle, respectively, v_t , a_t and j_t are velocity, acceleration and jerk of the subject vehicle; g_{\min}^{CM}

Figure 4 Merging scenario of multilane freeways



Notes: (a) Multilane freeways with CAV-only; 17 system could reduce unutilized roadway capacity and increase merging throughput, but no numerical/simulation experiment carried out.

and d_{min} are the minimum time headway and distance headway during merging; Δt^{CM} is the merging length of the time interval. The simulation showed that the comprehensive strategy outperformed the original strategy to reduce delay and increase vehicle speed. Liu *et al.* (2021) also integrated a lane selection model with the trajectory planning problem to account for the unevenness between lanes. The lane selection model used a reinforcement learning approach to output the lane choice decision of each vehicle based on the real-time traffic flow conditions.

Moreover, recent studies shed light on the more complicated situations where CAVs and HDVs coexist in a multilane merging area. Gao *et al.* (2021) developed an optimization-based trajectory planning strategy that enabled flexible choices of the mainline facilitating vehicle and the merging point. The strategy was tested under various CAV penetration rates in a two-lane freeway merging area. Williams *et al.* (2021) considered the challenging situation where vehicles may freely change lanes on a multilane freeway, especially with the presence of uncontrolled HDVs, so that the coordinated mainline vehicles may vary over time. The study proposed a mechanism to update the merging sequence and accounted for deviations in the measured vehicle positions in real-time to address this issue. Guo *et al.* (2020) developed a reinforcement learning approach for lane change control at freeway on-ramps and off-ramps. The automated agents took the speed of a vehicle and its distances to the surrounding vehicles (in the current and adjacent lanes) as inputs and output the decisions of speed (increase/decrease speed) and lane-change (keep the current lane or change). Recent studies considered the macroscopic traffic flow performance and proposed strategies that integrate multiple control measures at on-ramps. For example, Tajdari *et al.* (2020) combined lane-changing control enabled by CAVs with the conventional ramp metering strategy. Based on a cell-based traffic flow model, the combined strategy sought to keep the bottleneck density at the critical density level for maximized throughput by deciding the lane-changing flows between lanes and the ramp inflow rate. Adopting a similar idea, Pan *et al.* (2021) integrated ramp metering, variable speed control and lane change control for CAVs and the corresponding recommendations to HDVs in a merging control system. The strategy explicitly considers the stability of traffic flow and the compliance rate of human drivers. Numerical experiments show clear benefits of the strategy in terms of traffic efficiency, energy use and emissions.

5. Future research directions

Based on the comprehensive review of existing studies in the field of CAV ramp merging coordination, the following research gaps are identified:

- Most previous studies of CAV ramp merging have focused on the lower-level design of vehicle trajectories. In contrast, some have considered the upper-level decisions, such as selecting merging sequence and merging gap. In addition, only a few studies have addressed the development of control strategies at the traffic flow level. Therefore, a comprehensive system considering various essential elements of both control levels is needed.

- The existing strategies for mixed traffic conditions usually make simple assumptions on the driving patterns of HDVs. For example, the strategies assume that the HDVs strictly follow specific predefined driving rules without errors, delays or variances in the human driver population. Unfortunately, these assumptions tend to underestimate the uncertainties induced by HDVs and overestimate the cooperation willingness of human drivers.
- Most existing strategies for mixed traffic flow regard HDVs as only an uncontrolled external factor that restricts CAV behaviors, while the possibilities to influence the behaviors of HDVs for enhanced coordination benefits are not explored.
- As the multilane control problem is relatively complicated, many existing strategies only propose solutions in a discrete decision space (e.g. increase/decrease one step in speed and change lane or not). Therefore, more sophisticated coordination strategies in both the longitudinal and lateral directions, based on a thorough analysis of the consequences at the traffic flow level, should be further investigated.

6. Concluding remarks

This paper has presented a comprehensive review of the existing freeway ramp merging strategies leveraging CAVs, focusing on the latest trends and developments in the field. Based on the application context, the strategies are divided into three categories:

- 1 strategies involving CAV-only merging into one-lane;
- 2 strategies for mixed traffic flow merging into one-lane; and
- 3 strategies for CAV-only or mixed traffic flow merging into multilanes.

The findings based on the review can be summarized as follows:

Prior studies on CAV merging coordination tend to simplify the merging context and assume single-lane freeway layouts with a total CAV penetration rate. In the simplified contexts, the free lane-changing behaviors on the main road and the uncertainties induced by the uncontrolled HDVs are ignored. These considerations are continually accommodated in recent research efforts. Studies considering the presence of HDVs are devoted to predicting the intentions/behaviors of HDVs and use the predictions as inputs for the CAV control plan. In multilane freeway configurations, proactive lane-changing decisions of mainline CAVs are included in the control framework to fully use the bottleneck capacity and increase the overall performance of ramp merging operation.

Optimization is the most widely used method to solve the CAV merging problem, especially for the trajectory planning problem. The objectives of the optimization models favor different performance indexes, such as traffic efficiency, safety, energy use and passenger comfort, while being subject to constraints on vehicle dynamics, technical limits, safety constraints and requirements on traffic flow operation. Recent studies explored the possibilities of applying other methods to CAV merging control, such as machine learning, game theory and feedback control. A combination of multiple methods is

also used in a few studies (Guo *et al.*, 2020; Hang *et al.*, 2021; Liu *et al.*, 2021).

Most of the existing studies of CAV ramp merging emphasize lower-level controls such as trajectory planning. Even though some studies addressed upper-level controls for one-lane freeways with CAV-only, very limited studies have conducted optimization for upper-level and traffic flow controls for multilane merging and one-lane freeways with mixed traffic, which are the reasons why we do not review upper-level and lower-level controls separately for one-lane freeways with mixed traffic in Section 3 and multilane merging in Section 4. Therefore, more efforts in these streams should be made to improve robust on-ramp merging controls for multilane configurations and mixed traffic that are rather common in the forthcoming future.

Despite the comprehensive review presented in this paper, the study has some limitations. First, the review focuses on recent developments in CAV ramp merging coordination. However, some earlier studies regarding automated highway systems (Ioannou, 2013; Easa, 2007), for example, are not included in the scope of the review. Instead, the reader is referred to Scarinci and Heydecker (2014) and Rios-Torres and Malikopoulos (2017b) for an excellent review of prior works. Second, this review focuses on the CAV on-ramp merging situation studies. However, further studies covering the strategies for comparable situations, such as merging at work zones (Cao *et al.*, 2021), lane drops (Zhang *et al.*, 2019) and lane change at off-ramps and weaving sections (Zheng, 2014; Amini *et al.*, 2021; Nagalur Subraveti *et al.*, 2021) may benefit the overall understanding of CAV merging problem in general. Therefore, a survey including such studies is part of our ongoing review plan.

Note

1. The search covers relevant papers published since 2017 in the following journals: *Computer-Aided Civil and Infrastructure Engineering*, *IEEE Vehicular Technology Magazine*, *Transport Reviews*, *Transportation Research Part C: Emerging Technologies*, *Vehicular Communications*, *Transportation Research Part E: Logistics and Transportation Review*, *IEEE Transactions on Intelligent Transportation Systems*, *IEEE Transactions on Vehicular Technology*, *Transportation Research Part B: Methodological*, *Transportation Research Part A: Policy and Practice*, *Transportation Research Part D: Transport and Environment*, *Transportation*, *Journal of Intelligent Transportation Systems*, *Transportation Science*, *Transportation Letters*, *Journal of Intelligent and Connected Vehicles*, *IEEE Intelligent Transportation Systems Magazine*, *IEEE Transactions on Intelligent Vehicles* and *Journal of Transportation Engineering*, Part A: Systems, as well as other highly cited articles in the relevant field.

References

Ahn, S., Bertini, R.L., Auffray, B., Ross, J.H. and Eshel, O. (2007), "Evaluating benefits of systemwide adaptive ramp-metering strategy in Portland, Oregon", *Transportation*

Research Record: Journal of the Transportation Research Board, Vol. 2012 No. 1, pp. 47–56.

Ali, Y., Zheng, Z. and Haque, M.M. (2021), "Modelling lane-changing execution behavior in a connected environment: a grouped random parameters with heterogeneity-in-means approach", *Communications in Transportation Research*, Vol. 1, p. 100009.

Amini, E., Omidvar, A. and Elefteriadou, L. (2021), "Optimizing operations at freeway weaves with connected and automated vehicles", *Transportation Research Part C: Emerging Technologies*, Vol. 126, p. 103072.

Bevly, D., Cao, X., Gordon, M., Ozbilgin, G., Kari, D., Nelson, B., Woodruff, J., Barth, M., Murray, C., Kurt, A., Redmill, K. and Ozguner, U. (2016), "Lane change and merge maneuvers for connected and automated vehicles: a survey", *IEEE Transactions on Intelligent Vehicles*, Vol. 1 No. 1, pp. 105–120.

Cao, D., Wu, J., Wu, J., Kulcsár, B. and Qu, X. (2021), "A platoon regulation algorithm to improve the traffic performance of highway work zones", *Computer-Aided Civil and Infrastructure Engineering*, Vol. 36 No. 7, pp. 941–956.

Cao, W., Mukai, M., Kawabe, T., Nishira, H. and Fujiki, N. (2015), "Cooperative vehicle path generation during merging using model predictive control with real-time optimization", *Control Engineering Practice*, Vol. 34, pp. 98–105.

Carlson, R.C., Papamichail, I., Papageorgiou, M. and Messmer, A. (2010), "Variable speed limits as a mainline metering device for freeways", *89th Annual Meeting Transportation Research Board, Washington, DC*.

Cassidy, M.J. and Bertini, R.L. (1999), "Some traffic features at freeway bottlenecks", *Transportation Research Part B: Methodological*, Vol. 33 No. 1, pp. 25–42.

Chen, D., Srivastava, A. and Ahn, S. (2021a), "Harnessing connected and automated vehicle technologies to control lane changes at freeway merge bottlenecks in mixed traffic", *Transportation Research Part C: Emerging Technologies*, Vol. 123, p. 102950.

Chen, N., van Arem, B., Alkim, T. and Wang, M. (2020), "A hierarchical model-based optimization control approach for cooperative merging by connected automated vehicles", *IEEE Transactions on Intelligent Transportation Systems*, Vol. 22 No. 12.

Chen, T., Wang, M., Gong, S., Zhou, Y. and Ran, B. (2021b), "Connected and automated vehicle distributed control for on-ramp merging scenario: a virtual rotation approach", *Transportation Research Part C: Emerging Technologies*, Vol. 133, p. 103451.

Chen, X., Li, T., Ma, Z. and Sun, J. (2021c), "Integrated mainline and ramp signal control for expressway on-ramp bottleneck with unequal lane-setting", *Journal of Intelligent Transportation Systems*, Vol. 26 No. 1, pp. 100–115.

Ding, J., Peng, H., Zhang, Y. and Li, L. (2019), "Penetration effect of connected and automated vehicles on cooperative on-ramp merging", *IET Intelligent Transport Systems*, Vol. 14 No. 1, pp. 56–64.

Ding, J., Li, L., Peng, H. and Zhang, Y. (2020), "A rule-based cooperative merging strategy for connected and automated vehicles", *IEEE Transactions on Intelligent Transportation Systems*, Vol. 21 No. 8, pp. 3436–3446.

- Easa, S. (2007), "Automated highways", *Encyclopedia of Electrical and Electronics Engineering*, John Wiley & Sons, New York, NY.
- Fukuyama, S. (2020), "Dynamic game-based approach for optimizing merging vehicle trajectories using time-expanded decision diagram", *Transportation Research Part C: Emerging Technologies*, Vol. 120, p. 102766.
- Gao, Z., Wu, Z., Hao, W., Long, K., Byon, Y.-J. and Long, K. (2021), "Optimal trajectory planning of connected and automated vehicles at on-ramp merging area", *IEEE Transactions on Intelligent Transportation Systems*, Oct. 8, pp. 1-13, doi: [10.1109/TITS.2021.3116666](https://doi.org/10.1109/TITS.2021.3116666).
- Guo, J., Cheng, S. and Liu, Y. (2020), "Merging and diverging impact on mixed traffic of regular and autonomous vehicles", *IEEE Transactions on Intelligent Transportation Systems*, Vol. 22 No. 3, pp. 1639-1649.
- Haj-Salem, H., Farhi, N. and Lebacque, J.-P. (2014), "Combining ramp metering and hard shoulder strategies: field evaluation results on the Ile de France motorway network", *Transportation Research Procedia*, Vol. 3, pp. 1002-1010.
- Han, Y. and Ahn, S. (2018), "Stochastic modeling of breakdown at freeway merge bottleneck and traffic control method using connected automated vehicle", *Transportation Research Part B: Methodological*, Vol. 107, pp. 146-166.
- Hang, P., Lv, C., Huang, C., Xing, Y. and Hu, Z. (2021), "Cooperative decision making of connected automated vehicles at multilane merging zone: a coalitional game approach", *IEEE Transactions on Intelligent Transportation Systems*, pp. 1-13.
- Hu, X. and Sun, J. (2019), "Trajectory optimization of connected and autonomous vehicles at a multilane freeway merging area", *Transportation Research Part C: Emerging Technologies*, Vol. 101, pp. 111-125.
- Hu, Z., Huang, J., Yang, Z. and Zhong, Z. (2021), "Embedding robust constraint-following control in cooperative on-ramp merging", *IEEE Transactions on Vehicular Technology*, Vol. 70 No. 1, pp. 133-145.
- Ioannou, P. (Ed.), (2013), *Automated Highway System*, Springer, New York, NY.
- Ito, Y., Kamal, M.A.S., Yoshimura, T. and Azuma, S.-I. (2019), "Coordination of connected vehicles on merging roads using pseudo-perturbation-based broadcast control", *IEEE Transactions on Intelligent Transportation Systems*, Vol. 20 No. 9, pp. 3496-3512.
- Jin, P.J., Fang, J., Jiang, X., DeGaspari, M. and Walton, C.M. (2017), "Gap metering for active traffic control at freeway merging sections", *Journal of Intelligent Transportation Systems*, Vol. 21 No. 1, pp. 1-11.
- Jing, S., Hui, F., Zhao, X., Rios-Torres, J. and Khattak, A.J. (2019), "Cooperative game approach to optimal merging sequence and on-Ramp merging control of connected and automated vehicles", *IEEE Transactions on Intelligent Transportation Systems*, Vol. 20 No. 11, pp. 4234-4244.
- Karbalaieali, S., Osman, O.A. and Ishak, S. (2020), "A dynamic adaptive algorithm for merging into platoons in connected automated environments", *IEEE Transactions on Intelligent Transportation Systems*, Vol. 21 No. 10, pp. 4111-4122.
- Karimi, M., Roncoli, C., Alecsandru, C. and Papageorgiou, M. (2020), "Cooperative merging control via trajectory optimization in mixed vehicular traffic", *Transportation Research Part C: Emerging Technologies*, Vol. 116, p. 102663.
- Kherroubi, Z.E.A., Aknine, S. and Bacha, R. (2021), "Novel decision-making strategy for connected and autonomous vehicles in highway on-ramp merging", *IEEE Transactions on Intelligent Transportation Systems*, Oct. 4, pp. 1-13, doi: [10.1109/TITS.2021.3116666](https://doi.org/10.1109/TITS.2021.3116666).
- Larsson, J., Keskin, M.F., Peng, B., Kulcsár, B. and Wymeersch, H. (2021), "Pro-social control of connected automated vehicles in mixed-autonomy multilane highway traffic", *Communications in Transportation Research*, Vol. 1, p. 100019.
- Letter, C. and Eleftheriadou, L. (2017), "Efficient control of fully automated connected vehicles at freeway merge segments", *Transportation Research Part C: Emerging Technologies*, Vol. 80, pp. 190-205.
- Li, Y., Chow, A.H.F. and Cassel, D.L. (2014), "Optimal control of motorways by ramp metering, variable speed limits, and hard-shoulder running", *Transportation Research Record: Journal of the Transportation Research Board*, Vol. 2470 No. 1, pp. 122-130.
- Liao, X., Wang, Z., Zhao, X., Han, K., Tiwari, P., Barth, M.J. and Wu, G. (2021), "Cooperative ramp merging design and field implementation: a digital twin approach based on vehicle-to-cloud communication", *IEEE Transactions on Intelligent Transportation Systems*.
- Liu, J., Zhao, W. and Xu, C. (2021), "An efficient on-ramp merging strategy for connected and automated vehicles in multilane traffic", *IEEE Transactions on Intelligent Transportation Systems*, pp. 1-12, Jan. 8, doi: [10.1109/TITS.2020.3046643](https://doi.org/10.1109/TITS.2020.3046643).
- Lu, C. and Liu, C. (2021), "Ecological control strategy for cooperative autonomous vehicle in mixed traffic considering linear stability", *Journal of Intelligent and Connected Vehicles*, Vol. 4 No. 3, pp. 115-124.
- Marinescu, D., Čurn, J., Bouroche, M. and Cahill, V. (2012), "On-ramp traffic merging using cooperative intelligent vehicles: a slot-based approach", *15th International IEEE Conference on Intelligent Transportation Systems*, IEEE.
- Mergia, W.Y., Eustace, D., Chimba, D. and Qumsiyeh, M. (2013), "Exploring factors contributing to injury severity at freeway merging and diverging locations in Ohio", *Accident Analysis & Prevention*, Vol. 55, pp. 202-210.
- Milanés, V., Godoy, J., Villagrà, J. and Pérez, J. (2010), "Automated on-ramp merging system for congested traffic situations", *IEEE Transactions on Intelligent Transportation Systems*, Vol. 12 No. 2, pp. 500-508.
- Mu, C., Du, L. and Zhao, X. (2021), "Event-triggered rolling horizon-based systematical trajectory planning for merging platoons at mainline-ramp intersection", *Transportation Research Part C: Emerging Technologies*, Vol. 125, p. 103006.
- Nagalur Subraveti, H.H.S., Srivastava, A., Ahn, S., Knoop, V. L. and van Arem, B. (2021), "On lane assignment of connected automated vehicles: strategies to improve traffic flow at diverge and weave bottlenecks", *Transportation Research Part C: Emerging Technologies*, Vol. 127, p. 103126.
- Nishi, T., Doshi, P. and Prokhorov, D. (2019), "Merging in congested freeway traffic using multipolicy decision making

- and passive actor-critic learning”, *IEEE Transactions on Intelligent Vehicles*, Vol. 4 No. 2, pp. 287–297.
- Ntousakis, I.A., Nikolos, I.K. and Papageorgiou, M. (2016), “Optimal vehicle trajectory planning in the context of cooperative merging on highways”, *Transportation Research Part C: Emerging Technologies*, Vol. 71, pp. 464–488.
- Okuda, H., Suzuki, T., Harada, K., Saigo, S. and Inoue, S. (2021), “Quantitative driver acceptance modeling for merging car at highway junction and its application to the design of merging behavior control”, *IEEE Transactions on Intelligent Transportation Systems*, Vol. 22 No. 1, pp. 329–340.
- Omidvar, A., Elefteriadou, L., Pourmehrab, M. and Letter, C. (2020), “Optimizing freeway merge operations under conventional and automated vehicle traffic”, *Journal of Transportation Engineering, Part A: Systems*, Vol. 146 No. 7, p. 4020059.
- Pan, T., Guo, R., Lam, W.H.K., Zhong, R., Wang, W. and He, B. (2021), “Integrated optimal control strategies for freeway traffic mixed with connected automated vehicles: a model-based reinforcement learning approach”, *Transportation Research Part C: Emerging Technologies*, Vol. 123, p. 102987.
- Papageorgiou, M., Hadj-Salem, H. and Blosseville, J.-M. (1991), “ALINEA: a local feedback control law for on-ramp metering”, *Transportation Research Record*, Vol. 1320 No. 1, pp. 58–67.
- Papageorgiou, M., Hadj-Salem, H. and Middelham, F. (1997), “ALINEA local ramp metering: summary of field results”, *Transportation Research Record: Journal of the Transportation Research Board*, Vol. 1603 No. 1, pp. 90–98.
- Papamichail, I., Papageorgiou, M., Vong, V. and Gaffney, J. (2010), “Heuristic ramp-metering coordination strategy implemented at Monash freeway, Australia”, *Transportation Research Record: Journal of the Transportation Research Board*, Vol. 2178 No. 1, pp. 10–20.
- Pei, H., Feng, S., Zhang, Y. and Yao, D. (2019), “A cooperative driving strategy for merging at on-ramps based on dynamic programming”, *IEEE Transactions on Vehicular Technology*, Vol. 68 No. 12, pp. 11646–11656.
- Peng, B., Keskin, M.F., Kulcsár, B. and Wymeersch, H. (2021), “Connected autonomous vehicles for improving mixed traffic efficiency in unsignalized intersections with deep reinforcement learning”, *Communications in Transportation Research*, Vol. 1, p. 100017.
- Rios-Torres, J. and Malikopoulos, A.A. (2017a), “Automated and cooperative vehicle merging at highway on-ramps”, *IEEE Transactions on Intelligent Transportation Systems*, Vol. 18 No. 4, pp. 780–789.
- Rios-Torres, J. and Malikopoulos, A.A. (2017b), “A survey on the coordination of connected and automated vehicles at intersections and merging at highway on-ramps”, *IEEE Transactions on Intelligent Transportation Systems*, Vol. 18 No. 5, pp. 1066–1077.
- Rios-Torres, J. and Malikopoulos, A.A. (2018), “Impact of partial penetrations of connected and automated vehicles on fuel consumption and traffic flow”, *IEEE Transactions on Intelligent Vehicles*, Vol. 3 No. 4, pp. 453–462.
- Scarinci, R. and Heydecker, B. (2014), “Control concepts for facilitating motorway on-ramp merging using intelligent vehicles”, *Transport Reviews*, Vol. 34 No. 6, pp. 775–797.
- Scarinci, R., Heydecker, B. and Hegyi, A. (2015), “Analysis of traffic performance of a merging assistant strategy using cooperative vehicles”, *IEEE Transactions on Intelligent Transportation Systems*, Vol. 16 No. 4, pp. 2094–2103.
- Scarinci, R., Hegyi, A. and Heydecker, B. (2017), “Definition of a merging assistant strategy using intelligent vehicles”, *Transportation Research Part C: Emerging Technologies*, Vol. 82, pp. 161–179.
- Sonbolestan, M.-R., Monajjem, S. and Rouhani, E. (2021), “Impact of optimal selection of merging position on fuel consumption at highway on-ramps”, *Journal of Transportation Engineering, Part A: Systems*, Vol. 147 No. 5, p. 4021023.
- Srivastava, A. and Geroliminis, N. (2013), “Empirical observations of capacity drop in freeway merges with ramp control and integration in a first-order model”, *Transportation Research Part C: Emerging Technologies*, Vol. 30, pp. 161–177.
- Sun, Z., Huang, T. and Zhang, P. (2020), “Cooperative decision-making for mixed traffic: a ramp merging example”, *Transportation Research Part C: Emerging Technologies*, Vol. 120, p. 102764.
- Tajdari, F., Roncoli, C. and Papageorgiou, M. (2020), “Feedback-based ramp metering and lane-changing control with connected and automated vehicles”, *IEEE Transactions on Intelligent Transportation Systems*, Vol. 23 No. 2, pp. 939–951.
- Wang, L., Abdel-Aty, M., Lee, J. and Shi, Q. (2019), “Analysis of real-time crash risk for expressway ramps using traffic, geometric, trip generation, and socio-demographic predictors”, *Accident Analysis & Prevention*, Vol. 122, pp. 378–384.
- Wang, Y., Wenjuan, E., Tang, W., Tian, D., Lu, G. and Yu, G. (2013), “Automated on-ramp merging control algorithm based on internet-connected vehicles”, *IET Intelligent Transport Systems*, Vol. 7 No. 4, pp. 371–379.
- Ward, E., Evstedt, N., Axehill, D. and Folkesson, J. (2017), “Probabilistic model for interaction aware planning in merge scenarios”, *IEEE Transactions on Intelligent Vehicles*, Vol. 2 No. 2, pp. 133–146.
- Williams, N., Wu, G. and Barth, M. (2021), “Position uncertainty-tolerant cooperative merging application for mixed multilane traffic”, *IEEE Transactions on Intelligent Vehicles*, Oct. 19, doi: [10.1109/TIV.2021.3120751](https://doi.org/10.1109/TIV.2021.3120751).
- Xie, Y., Zhang, H., Gartner, N.H. and Arsava, T. (2017), “Collaborative merging strategy for freeway ramp operations in a connected and autonomous vehicles environment”, *Journal of Intelligent Transportation Systems*, Vol. 21 No. 2, pp. 136–147.
- Xu, F. and Shen, T. (2021), “Decentralized optimal merging control with optimization of energy consumption for connected hybrid electric vehicles”, *IEEE Transactions on Intelligent Transportation Systems*, Feb. 03, pp. 1–13, doi: [10.1109/TITS.2021.3054903](https://doi.org/10.1109/TITS.2021.3054903).
- Xu, H., Feng, S., Zhang, Y. and Li, L. (2019a), “A grouping-based cooperative driving strategy for CAVs merging problems”, *IEEE Transactions on Vehicular Technology*, Vol. 68 No. 6, pp. 6125–6136.
- Xu, L., Lu, J., Ran, B., Yang, F. and Zhang, J. (2019b), “Cooperative merging strategy for connected vehicles at highway on-ramps”, *Journal of Transportation Engineering, Part A: Systems*, Vol. 145 No. 6, p. 4019022.

- Zhang, C., Sabar, N.R., Chung, E., Bhaskar, A. and Guo, X. (2019), "Optimization of lane-changing advisory at the motorway lane drop bottleneck", *Transportation Research Part C: Emerging Technologies*, Vol. 106, pp. 303-316.
- Zhang, L., Zhang, L., Hale, D.K., Hu, J. and Huang, Z. (2017), "Cycle-based variable speed limit methodology for improved freeway merging", *IET Intelligent Transport Systems*, Vol. 11 No. 10, pp. 632-640.
- Zhang, Z. and Yang, X.T. (2021), "Analysis of highway performance under mixed connected and regular vehicle environment", *Journal of Intelligent and Connected Vehicles*, Vol. 4 No. 2, pp. 68-79.
- Zheng, Z. (2014), "Recent developments and research needs in modeling lane changing", *Transportation Research Part B: Methodological*, Vol. 60, pp. 16-32.
- Zhou, M., Qu, X. and Jin, S. (2017), "On the impact of cooperative autonomous vehicles in improving freeway merging: a modified intelligent driver model-based approach", *IEEE Transactions on Intelligent Transportation Systems*, Vol. 18 No. 6, pp. 1422-1428.
- Zhou, Y., Cholette, M.E., Bhaskar, A. and Chung, E. (2019a), "Optimal vehicle trajectory planning with control constraints and recursive implementation for automated on-ramp merging", *IEEE Transactions on Intelligent Transportation Systems*, Vol. 20 No. 9, pp. 3409-3420.
- Zhou, Y., Chung, E., Bhaskar, A. and Cholette, M.E. (2019b), "A state-constrained optimal control-based trajectory planning strategy for cooperative freeway mainline facilitating and on-ramp merging maneuvers under congested traffic", *Transportation Research Part C: Emerging Technologies*, Vol. 109, pp. 321-342.

Corresponding author

Kun Gao can be contacted at: kgun@chalmers.se