Smart Electric Vehicle Charging Approaches for Demand Response

Downloaded from: https://research.chalmers.se, 2026-11-14 20:38 UTC

Citation for the original published paper (version of record):
Diaz-Londono, C., Li, Y. (2024). Smart Electric Vehicle Charging Approaches for Demand Response. Energies, 17(24). http://dx.doi.org/10.3390/en17246273

N.B. When citing this work, cite the original published paper.

research.chalmers.se offers the possibility of retrieving research publications produced at Chalmers University of Technology. It covers all kind of research output: articles, dissertations, conference papers, reports etc. since 2004. research.chalmers.se is administrated and maintained by Chalmers Library

(article starts on next page)

energies

MDPI

Editorial

Smart Electric Vehicle Charging Approaches for Demand Response

Cesar Diaz-Londono [1,*] and Yang Li [2]

[1] Dipartimento di Elettronica, Informazione e Bioingegneria, Politecnico di Milano, Piazza Leonardo da Vinci, 32, 20133 Milano, Italy
[2] Department of Electrical Engineering, Chalmers University of Technology, 412 96 Gothenburg, Sweden; yangli@ieee.org
* Correspondence: cesar.diaz@ieee.org

This editorial explores the recent advancements in the field of smart Electric Vehicle (EV) charging approaches, particularly in the context of demand response. As EVs become increasingly integrated into the power grid, significant challenges arise in maintaining the balance between supply and demand. These challenges require the development of innovative charging strategies that not only offer energy flexibility but also predict and optimize the charging behaviors of EVs connected to charging infrastructure.

Smart charging strategies, including unidirectional (V1G) and bidirectional (V2G) approaches, offer a means to better manage demand peaks, enhance grid reliability, and improve power quality. According to [1], the strategic placement of EV charging stations is crucial for optimizing grid operations, urban planning, and customer convenience. This study underscores the importance of location analysis in maximizing accessibility while minimizing the stress on local grids.

Incorporating renewable energy sources into EV charging infrastructure is equally critical. Solar photovoltaic (PV) systems, for instance, can support local grid stability while reducing reliance on fossil fuels. Reference [2] illustrates the effectiveness of smart charging technologies in achieving peak shaving and cost savings when integrated with PV systems. Bidirectional charging, in particular, enhances these benefits, achieving up to 8.1% additional cost efficiency compared to unidirectional systems. These findings emphasize the role of advanced energy management strategies in fostering sustainable urban mobility.

Moreover, innovative planning approaches are required to address the growing demand for EV charging infrastructure. Reference [3] presents an optimization model for reconfigurable EV chargers, which reduces both investment and operational costs in large car parks while meeting diverse energy needs. Such strategies highlight the potential of flexible and scalable solutions to adapt to varying energy demands across different regions.

1. Advanced Control and Optimization Techniques

The role of advanced control strategies and optimization algorithms in EV integration cannot be overstated. These technologies ensure the efficient operation of EVs and their seamless interaction with the grid. Reference [4] explores how EVs can contribute to grid reliability by compensating for the inherent variability of renewable energy sources, such as wind and solar. By leveraging EV batteries as distributed energy resources, grids can achieve greater stability even under fluctuating conditions.

Another critical aspect is improving the energy efficiency of EVs through real-time control. Nonlinear Model Predictive Control (NMPC), as discussed in [5], provides a practical framework for optimizing energy consumption. By adapting to dynamic driving profiles and environmental conditions, NMPC extends EV range and reduces overall energy use. These advancements are instrumental in enhancing the practicality and affordability of electric mobility.

check for updates

Citation: Diaz-Londono, C.; Li, Y. Smart Electric Vehicle Charging Approaches for Demand Response. *Energies* **2024**, *17*, 6273. https://doi.org/10.3390/en17246273

Received: 29 November 2024
Accepted: 9 December 2024
Published: 12 December 2024

Copyright: © 2024 by the authors. Licensee MDPI, Basel, Switzerland. This article is an open access article distributed under the terms and conditions of the Creative Commons Attribution (CC BY) license (https://creativecommons.org/licenses/by/4.0/).

However, the increasing use of EVs also raises concerns about power quality. Harmonics generated by multiple chargers operating simultaneously can affect grid stability and equipment performance. Reference [6] investigates these issues and provides insights into mitigating the impact of harmonic distortion. By addressing these technical challenges, researchers are paving the way for a more resilient and reliable charging ecosystem.

2. Energy Markets and Peer-to-Peer Transactions

Beyond technical optimization, integrating EVs into energy markets presents an opportunity for innovative business models. Reference [7] examines advanced DC-DC converters, which enable efficient energy storage and transfer, enhancing the operational capabilities of EV charging systems. Meanwhile, accurate battery management systems, as highlighted in [8], are crucial for ensuring transparency in capacity estimation and overall system performance.

Peer-to-peer (P2P) energy trading further expands the potential of EVs in modern energy systems. Reference [9] highlights the benefits of P2P transactions in industrial multi-energy hubs, demonstrating how these systems can enhance flexibility and reduce risk. By allowing decentralized energy trading among EV users, renewable energy generators, and other stakeholders, these models foster a collaborative approach to energy management that benefits all participants.

3. Enhancing Community Resilience

The integration of EVs into local energy systems is not only about efficiency but also resilience. During grid disturbances or natural disasters, bi-directional EV operations can provide critical backup power to residential communities. Reference [10] proposes a resiliency-sensitive decision-making mechanism that incorporates fuel-cell EVs in V2G mode. This approach ensures energy stability and supports local grids during abnormal conditions, offering a lifeline for communities in crisis.

Moreover, distributed energy resources, such as solar panels and battery storage systems, can work synergistically with EVs to create self-sustaining energy ecosystems. By leveraging these technologies, communities can reduce their dependence on centralized grids and enhance their ability to recover from disruptions.

4. Remarks

The integration of EVs into power grids represents a pivotal moment in the transition toward a sustainable energy future. Through smart charging strategies, advanced optimization techniques, and innovative market models, EVs can transform energy systems to be more efficient, resilient, and environmentally friendly. While challenges remain—particularly in ensuring power quality and managing infrastructure demands—ongoing research and technological advancements continue to address these obstacles.

Ultimately, the widespread adoption of EVs and their seamless integration into the grid depend on a holistic approach that balances technical innovation, market mechanisms, and community resilience. As evidenced by the studies cited, progress in this field not only enhances the viability of electric mobility but also contributes to a cleaner and more sustainable world.

Funding: This research received no external funding.

Conflicts of Interest: The authors declare no conflicts of interest.

References

1. Mazza, A.; Russo, A.; Chicco, G.; Di Martino, A.; Colombo, C.; Longo, M.; Ciliento, P.; De Donno, M.; Mapelli, F.; Lamberti, F. Categorization of Attributes and Features for the Location of Electric Vehicle Charging Stations. *Energies* **2024**, *17*, 3920. [CrossRef]
2. Meiers, J.; Frey, G. A Case Study of the Use of Smart EV Charging for Peak Shaving in Local Area Grids. *Energies* **2024**, *17*, 47. [CrossRef]

3. Song, B.; Madawala, U.; Baguley, C. Optimal Planning Strategy for Reconfigurable Electric Vehicle Chargers in Car Parks. *Energies* **2023**, *16*, 7204. [CrossRef]
4. Ullah, Z.; Ullah, K.; Diaz-Londono, C.; Gruosso, G.; Basit, A. Enhancing Grid Operation with Electric Vehicle Integration in Automatic Generation Control. *Energies* **2023**, *16*, 7118. [CrossRef]
5. Bello, Y.; Roncancio, J.; Azib, T.; Patino, D.; Larouci, C.; Boukhnifer, M.; Rizoug, N.; Ruiz, F. Practical Nonlinear Model Predictive Control for Improving Two-Wheel Vehicle Energy Consumption. *Energies* **2023**, *16*, 1950. [CrossRef]
6. Mazza, A.; Benedetto, G.; Bompard, E.; Nobile, C.; Pons, E.; Tosco, P.; Zampolli, M.; Jaboeuf, R. Interaction Among Multiple Electric Vehicle Chargers: Measurements on Harmonics and Power Quality Issues. *Energies* **2023**, *16*, 7051. [CrossRef]
7. Bathala, K.; Kishan, D.; Harischandrappa, N. Soft Switched Current Fed Dual Active Bridge Isolated Bidirectional Series Resonant DC-DC Converter for Energy Storage Applications. *Energies* **2023**, *16*, 258. [CrossRef]
8. Calearo, L.; Ziras, C.; Thingvad, A.; Marinelli, M. Agnostic Battery Management System Capacity Estimation for Electric Vehicles. *Energies* **2022**, *15*, 9656. [CrossRef]
9. Valipour, E.; Nourollahi, R.; Taghizad-Tavana, K.; Nojavan, S.; Alizadeh, A. Risk Assessment of Industrial Energy Hubs and Peer-to-Peer Heat and Power Transaction in the Presence of Electric Vehicles. *Energies* **2022**, *15*, 8920. [CrossRef]
10. Erdinç, F.; Çiçek, A.; Erdinç, O. Resiliency-Sensitive Decision Making Mechanism for a Residential Community Enhanced with Bi-Directional Operation of Fuel Cell Electric Vehicles. *Energies* **2022**, *15*, 8729. [CrossRef]

Disclaimer/Publisher's Note: The statements, opinions and data contained in all publications are solely those of the individual author(s) and contributor(s) and not of MDPI and/or the editor(s). MDPI and/or the editor(s) disclaim responsibility for any injury to people or property resulting from any ideas, methods, instructions or products referred to in the content.