

Value-driven MBSE for evolving business contexts: a quantitative study on aerospace electrification

Downloaded from: https://research.chalmers.se, 2025-10-30 08:24 UTC

Citation for the original published paper (version of record):

Panarotto, M., Isaksson, O., Andersson, P. (2025). Value-driven MBSE for evolving business contexts: a quantitative study on aerospace electrification. Design Science, 11. http://dx.doi.org/10.1017/dsj.2025.10024

N.B. When citing this work, cite the original published paper.

research.chalmers.se offers the possibility of retrieving research publications produced at Chalmers University of Technology. It covers all kind of research output: articles, dissertations, conference papers, reports etc. since 2004. research.chalmers.se is administrated and maintained by Chalmers Library

Value-driven MBSE for evolving business contexts: a quantitative study on aerospace electrification

Massimo Panarotto D1, Ola Isaksson D2 and Petter Andersson3

Abstract

Changing environmental, societal, and business conditions shift the priority given to the 'most valuable' design solutions to be developed, which risks causing rework and mistakes during the development process. To maintain consistency among changes in what 'value' means in evolving business contexts, this paper presents a method – value-driven model-based systems engineering (VD-MBSE) – implemented in a software tool (named Club Design). The method is demonstrated through a case study related to aerospace electrification, highlighting its ability to maintain consistency during the iterations between business development and the design of technical solutions.

Keywords: Model-Based Systems Engineering, Requirements Traceability, Value Assessment, Value-Driven Design

1. Introduction

Product development seems to be increasingly affected by external conditions (e.g., key technological enablers, characteristics of the surrounding infrastructure, and value chain), which tend to evolve – and sometimes dramatically change – the priorities given to the 'most valuable' design solutions to be developed. The iteration and updates caused by shifts in priorities risk becoming time-consuming tasks and prone to mistakes for complex products composed of multiple subsystems and components. At the same time, the success of products is becoming increasingly dependent on non-functional value aspects which are not strictly related to the functionality of the product but have profound implications for the resources consumed during the product's lifecycle (e.g., flexibility in operation, environmental, and social sustainability). These non-functional aspects tend to be highly volatile during the course of a project (Morkos, Joshi & Summers 2019), due to the difficulty in finding measurable and verifiable requirements so that design solutions can be assessed on these aspects in a reliable manner.

To respond to these two challenges, we present a method – value-driven model-based systems engineering (VD-MBSE) – guided by the following research questions and associated hypotheses:

Received 04 November 2024 Revised 29 July 2025 Accepted 29 July 2025

Corresponding author
Massimo Panarotto
massimo.panarotto@polimi.it

© The Author(s), 2025. Published by Cambridge University Press. This is an Open Access article, distributed under the terms of the Creative Commons Attribution licence (http://creativecommons.org/licenses/by/4.0), which permits unrestricted re-use, distribution and reproduction, provided the original article is properly cited.

Des. Sci., vol. 11, e36 journals.cambridge.org/dsj DOI: 10.1017/dsj.2025.10024





¹Department of Mechanical Engineering, Politecnico di Milano, Milano, Italy

²Department of Industrial and Materials Science, Chalmers University of Technology, Gothenburg, Sweden

³GKN Aerospace Sweden AB, Trollhättan, Sweden

RQ 1: How to reduce the risk of design rework in the case of future changes in business contexts?

We hypothesize that the ability to simultaneously analyse the impact of multiple business contexts during the design phases reduces the risk of rework.

RQ 2: How to mitigate the risk of design rework caused by evolving requirements during development?

We hypothesize that the ability to quickly iterate value aspects, especially nonfunctional ones, reduces the risk of rework due to the volatility of requirements during the development process.

As such, the method exploits the traceability benefits of Model-Based Systems Engineering techniques (MBSE; ISO 24641 2023b), while addressing the need to explore alternatives both on the business side (leading to alternative needs and requirements) and the solution side (leading to design concepts of different types). To demonstrate and test the proposed method, VD-MBSE has been implemented in a novel software tool (Club Design) and applied to a case study in the aerospace industry. This sector is setting ambitious targets to significantly reduce, or even eliminate, carbon-based emissions and the associated climate impact. Novel technologies are expected to be integrated (e.g., electrical propulsion). In addition, new modes of transport (e.g., ultra-short regional aviation; Peciak & Skarka 2022), emerging legislation, and unforeseen disruptive events are making aerospace companies more dynamic. This is a clear case where it is critical to understand such prematurely defined business contexts (e.g., which missions, the type of customers, etc.), since there is a high risk that the design solutions developed today will not be optimal if the targeted business context changes in the meantime.

The next sections will describe VD-MBSE and Club Design, as presented in a case study where two companies – an OEM and its second-tier supplier – are tasked with the challenge of designing, in parallel, an electric aircraft and one engine component (a Fan Outlet Guide Vane, FOGV) for highly uncertain businesses such as regional and transnational flights. The aerospace context is chosen as test bed since for the manufacturers developing the electric aircraft, it is unclear which configurations will emerge and when. Operational targets are uncertain, ranging from traditional ranges (e.g., 1400 km) to new operational scenarios like ultra-short regional flights for tourism (under 200 km). Additionally, the target customer is undefined, with many start-ups potentially entering the market, each with differing development approaches.

The structure of this paper is organized as follows. Section 2 outlines the background and highlights the need to model alternative business cases and architectures concurrently. Section 3 introduces the proposed VD-MBSE method, along with the supporting modelling tool. Section 4 applies this method in the case study. Section 5 presents the outputs of the method, emphasizing the generation of compatible design sets aligned with evolving business contexts. Section 6 quantitatively positions VD-MBSE within the broader MBSE landscape. Section 7 discusses the findings, implications, and limitations of the approach. Finally, Section 8 concludes the paper by summarizing key contributions and suggesting directions for future work.

2. Background: the need to simultaneously model alternative business cases and architectures

Systems Engineering (SE) was developed as a means to keep consistency between the intended 'value' of a system (or its design intent) and the developed technical

solutions (Martin 1998; INCOSE 2023). As such, the definition of system requirements is one of the cornerstones of SE methodologies and standards, since requirements should convey a precise formulation of what should be developed. However, the translation between the 'value' of a system into measurable requirements is difficult, and requirements are often renegotiated, reformulated, and updated during the development process. MBSE (Wymore 1993; Yang, Cormican & Yu 2019; ISO 24641 2023b) has been proposed to ensure the consistency between changes in systems requirements and technical solutions through the use of software tools (Hehenberger *et al.* 2016; Huldt & Stenius 2019). Many industries are currently investing in MBSE, with commercial software tools such Magic-DrawTM and CapellaTM, where MagicDrawTM was acquired by Dassault SystèmesTM and further developed as CameoTM, and CapellaTM was adopted by SiemensTM and integrated with TeamcenterTM as System Modeling WorkbenchTM.

While these MBSE tools are currently used in industry, they are often used starting from a single targeted mission or business that has been defined beforehand (Honour 2010; Madni & Purohit 2019). There are a number of reasons that limit the application of MBSE in the business development stages. First, stakeholder 'values' are often expressed in natural language at varying levels of detail (Fantoni *et al.* 2021). They may be unspecific (e.g., 'being environmentally sustainable') or overly specific (e.g., 'the vane material must be stainless steel'), requiring reformulation into more general terms to avoid premature solutions. Moreover, not all system requirements can be defined beforehand. Particularly 'non-functional requirements' like flexibility and maintainability – often emerge once a solution is developed. Finally, the formulation of requirements can unintentionally suggest specific solutions, limiting innovation (Collopy & Hollingsworth 2011).

2.1. Existing MBSE approaches to manage stakeholder expectations to system solutions in early phase design

The reasons above led to the development of techniques to model the business and operational contexts at a more granular level than current MBSE methods. These techniques, defined under the more general terms of 'value modelling' 'value assessment,' and 'value-driven design' (Lavi & Reich 2024), have received attention in recent years, although there is not yet a universally established practice. Two distinct categories of value modelling methods can be distinguished: (1) those that focus on capturing value aspects to specify requirements and guide the generation of engineering solutions and (2) those that focus on assessing solutions based on a number of value aspects.

2.1.1. Techniques that focus on capturing value aspects

Through a series of aerospace enterprise collaboration research projects^{1,2} in Europe, an underlying value information model was developed (Isaksson *et al.* 2013) and applied to ensure that the governing intent of high-level expectations

¹Collaborative & Robust Engineering using Simulation Capability Enabling Next Design Optimisation | CRESCENDO | Project | News & Multimedia | FP7 | CORDIS | European Commission.

²Thermal Overall Integrated Conception of Aircraft | TOICA | Project | News & Multimedia | FP7 | CORDIS | European Commission.




Figure 1. Meta-model as a class diagram of the 'Value Model' by Isaksson et al. (2013).

and needs can be maintained throughout the requirements engineering process of large systems spanning several levels of a value chain. Figure 1 outlines the key definitions used in this model (represented as a UML Class Diagram), together with an example related to a transportation system.

The 'Value Creation Strategy' (VCS) describes a high-level context for the system to be developed. In transportation, this context could be formulated as 'early commuting to a congested city.' The VCS is formulated as a rank-weight of Stakeholders' Needs. A different rank-weight of the needs provides a different context for the development (therefore, multiple Value Creation Strategies can be communicated).

The Stakeholders' Needs are derived after interpreting the 'raw-data' statements of expectations from the stakeholders (gathered from interviews and focus groups). This raw data is captured as a stakeholder expectation. The reason for differentiating between expectations and needs is that, in a complex product, stakeholder statements vary in format and detail and often require validation to confirm correct expression and intent. This validation may occur after the project has already started, and a change in the expectation may require reformulation of the needs and may shift the trade-offs involved in the assessment of solutions.

In our example, the stakeholder formulates an over-specific expectation by already specifying a solution (e.g., the engine having low power). If an engineer wants to formulate a solution-independent version of this expectation, it could be interpreted as the need to reduce the time to perform office work. However, this interpretation needs to be confirmed, and it may be subject to change, with potentially profound cascading effects on the solutions targeted by the engineers.

For these reasons, Stakeholder Expectations and Needs are contained in two different information objects.

To start investigating solutions to fulfill the needs, value drivers (VDs) are formulated, which are alternative characteristics that can be determined by design to satisfy a stakeholder need. Still aiming to keep the design space as wide as possible, there is a 1:n relationship between a need and a VD. VDs can be considered the pre-stage of requirements and are kept as solution-independent as possible. In our example, system power has an impact on the need to reduce the time to start doing office work, but so does the number of communication systems (since the user can begin office work by communicating while in transit). After solutions (based on the VDs) are generated and evaluated, the VDs can be formalized as requirements.

2.1.2. Techniques that focus on assessing solutions on value aspects

Regarding the assessment of engineering solutions, there is a growing shift in value assessment methods from qualitative, expert-based approaches (e.g., Quality Function Deployment extensions; Bertoni, Bertoni & Isaksson 2018) to more quantitative, data-driven techniques. For instance, Donelli, Boggero & Nagel (2023) combined cost models with expert-based utility functions to assess aircraft wing assemblies, incorporating production time, quality, and risks. While utility cost curves are common in systems engineering trade-off analysis, a recent trend merges utility and cost into a single financial metric for easier comparison of business alternatives. Panarotto, Borgue & Isaksson (2020a) implemented the surplus value (SV) financial metric suggested by Collopy & Hollingsworth (2011) to simplify net present value (NPV) analysis in complex cross-company systems. Time factors also affect value and are often missed in expert-based evaluations. For example, Panarotto et al. (2020a) showed that a system optimized for earlier development – despite lower performance – can be more valuable due to earlier revenue generation. Thus, several approaches (e.g., Panarotto et al. 2020a; Pohya et al. 2021; Ramm et al. 2024) integrate NPV or SV analysis with discrete event simulations to model revenues and costs over a system's lifecycle. However, one issue when running these simulations is that they often use ad hoc lifecycle representations tailored to specific industry objectives. This means that the presented models are often based on specific applications and use cases. Reapplying these models to other technologies and applications can be time-consuming.

3. Proposed method and modelling tool – Value-driven model-based systems engineering (VD-MBSE)

To support both the process of simultaneously modelling alternative business contexts and architectures, VD-MBSE is proposed. VD-MBSE is used to simultaneously iterate business contexts, the associated needs, requirements, and design solutions throughout the development process. The method strives to progressively narrow down both design solutions and business options while ensuring compatibility, using a set-based concurrent engineering approach (Sobek, Ward & Liker 1999). More details about the set-based nature of the approach will be provided in Section 5. This approach ensures that even if business contexts change, the system's solutions remain adaptable. In early design stages, identifying the




Figure 2. Overall workflow of the proposed VD-MBSE method: the objective is to gradually narrow down the business design space and the solution design space over time.

range of design requirements that make a solution compatible is key to further developing sub-systems and components. The approach aims to connect business and solution design spaces through an MBSE structure. VD-MBSE is structured along four main steps that are repeated as more knowledge is gained (Figure 2).

VD-MBSE involves:

- Defining the business design space: Using 'Value Creation Strategies' (VCSs) to
 outline business scenarios that inform design studies. VCSs help translate
 stakeholder expectations (gathered through interviews and focus groups) into
 more concrete engineering problems. Stakeholder preferences are ranked and
 weighted for each business scenario.
- Defining VDs: VDs link stakeholder needs in the VCSs to design solutions, serving as early versions of design requirements and guiding solution exploration
- Defining the solution design space: Designs are created based on VDs or, conversely, design alternatives can update the VDs.
- Performing Value and Cost studies: Design solutions are evaluated against VCSs using a monetary approach, leveraging the Surplus Value model (Collopy & Hollingsworth 2011) integrated with ISO 15288 2023a and discrete event simulation to capture value changes over the system lifecycle. ISO/IEC 15288 provides a standardized framework for systems engineering processes throughout a system's life cycle. While it is not directly a simulation tool, ISO 15288 can be used to structure a discrete event simulation (DES) by defining the processes,




Figure 3. Main web interface of club design.

states, transitions, and resources involved in a system's development and operation.

To perform all these steps, the method has been implemented in a modeling tool (Club Design). Figure 3 shows the web interface of Club Design, which is organized into six different tabs. By clicking the tabs from left to right, users can go through all the steps defined in Figure 2. Full reference and log in details to Club Design can be provided upon request.

The next section will go through the four main steps to show the key features developed in VD-MBSE, as applied to an industrial case study.

Case study – Concurrent design of a Fan Outlet Guide Vane for electrification of aerospace products businesses

In this industrial case study, two companies – an OEM and its second-tier supplier – are tasked with the challenge of concurrently designing an electric aircraft and one engine component (a Fan Outlet Guide Vane – FOGV) for the electrification of aerospace product businesses. An FOGV is a component that establishes a structural linkage between the primary engine carcass and the aircraft's attachment point (i.e., a structural function), while also directing the flow emanating from the low-pressure turbine (i.e., an aerodynamic function). The challenges faced by the two companies can be introduced after reviewing Figure 4.

For the OEM developing the electric aircraft, it is unclear which operational scenarios will emerge and when. Operational targets are uncertain, ranging from traditional ranges (e.g., 1400 km) to new operational scenarios such as ultra-short regional flights for tourism (under 200 km). Additionally, the target customer is undefined, with many start-ups potentially entering the market, each with differing development approaches. Some start-ups may prioritize a radical development approach with quick, cost-effective solutions that compromise initial performance




Figure 4. Challenges for (a) the OEM and (b) the FOGV manufacturer, showing the position of the FOGV in the aircraft engine.

and risk (similar to an 'Aeronautic SpaceX' approach), while others may pursue a more traditional and risk-adverse development strategy.

These business uncertainties profoundly impact the FOGV manufacturer. Traditionally, development starts from mature requirements based on fixed engine and aircraft configurations. In the electrification of aerospace products, the uncertainty requires the aircraft and FOGV to be developed concurrently with the evolving business contexts. This evolution leads to changes and updates, affecting adjacent components and FOGV requirements. Consequently, the solution space must remain open, with flexibility to adapt designs as requirements shift. As targeted businesses evolve or are abandoned, it becomes crucial for the FOGV manufacturer to identify design alternatives that are compatible across various business strategies.

4.1. Define business design space

By moving to the leftmost tab in Club Design (VCS), users can define the 'Value Creation Strategies.' A VCS is defined as rank-weighted stakeholders' needs. An example of a VCS for the business scenario 'ultra-short flight' (< 200 km) is presented in Figure 5.

A VCS is represented in tabular form, where for each relevant stakeholder (e.g., the aircraft manufacturer and the FOGV manufacturer), the 'raw data' captured during interviews and focus groups (often in textual form and natural language) is translated into stakeholder needs that formulate a more concrete engineering problem to be solved. As this 'translation' is highly iterative, the tool supports modifications to maintain consistency. The final step in this process is to define rank-weights for the VCS (on the rightmost part of Figure 5). Many methods can be used to define the rank-weights, in this case study a pair-wise comparison has been used. More details about the created VCSs are provided in the next section. Once the first VCS is created, the 'duplicate' function can be used to create




Figure 5. One example of VCS as rank-weighted stakeholders needs for the VCS "ultra-short flight" (< 200 km).

additional VCSs and define more business scenarios. This is shown in Figure 6, taken from the 'spider chart' function of Club Design.

The focal points of Figure 6 are to show how the VCSs include external stakeholders' needs such as the OEM (e.g., 'reduce energy consumption,' formulated as 'energy consumption' in due to space constraints). These will later result in functional requirements to satisfy these needs (e.g., structural stiffness or noise). At the same time, the VCSs contain information regarding the concerns of internal stakeholders, such as the FOGV manufacturer (e.g., 'ability of multiple sourcing' or




Figure 6. Five VCSs defining different priorities for the design alternatives to investigate.

'increase environmental sustainability in manufacturing'). These will result in non-functional requirements for the solution.

The VCSs provide preliminary insights into stakeholders' preferences for design alternatives. For example, using ultra-light materials may reduce weight and energy consumption but limit supplier options, negatively impacting the manufacturer. For short flights, reduced energy consumption may outweigh the need for multiple sourcing, while in long-term scenarios like '100 years in service,' multiple sourcing becomes critical for supply chain resilience. It's important to note that VCS rank-weights do not dictate a specific design but encourage engineering teams to consider multiple business scenarios simultaneously, especially when the future direction is uncertain.

4.2. Define and update VDs


Although the VCSs provide high-level information about the solutions to be developed, engineers often require more precise and measurable requirements to begin investigating design solutions. As described in the background, VDs are introduced to provide a pre-stage of requirements for two main reasons:

- To allow room for some volatility in the formulation of requirements, enabling iteration of non-functional attributes of a design (often associated with development, manufacturing, and end-of-life aspects) until a more precise formulation is reached.
- To keep the requirement space as solution-independent as possible. While
 requirements are typically clear and detailed, they often implicitly suggest a
 specific solution direction, which may limit innovation capability (Collopy &
 Hollingsworth 2011).

Figure 7 provides examples illustrating the reasons for using value drivers in the FOGV case study.

The figure shows an excerpt of a value creation strategy for the 'ultra-short flight.' The VCS attempts to capture expectations, needs, and VDs for as many lifecycle phases as possible (e.g., design, manufacturing, operation, and maintenance). Each row in the VCS (starting with a stakeholder with an expectation) is connected to one of the 30 processes defined in the ISO 15288 standard. The reason to apply ISO/IEC/IEEE 15288:2023 (Dori 2024) is that it is a systems engineering standard that provides a common framework for describing system lifecycle processes and terminology. It applies to any level of a system's structure and can be referenced by anyone involved in system lifecycle or engineering activities. Therefore, ISO 15288 provides a cross-sectoral lifecycle representation of different products and systems, and for these reasons, it is used as the backbone of the software. The software allows users to select these processes via a drop-down menu and to define sub-processes. This specification of processes allows for the definition of a structure that will be crucial for the cost/value study performed using the discrete-event simulation algorithm (to be detailed in Section 4.4).

The focal point of Figure 7 is to highlight how the VCS contains VDs related to the operation and maintenance processes, which are typically the main interest of external stakeholders such as the OEM and the airlines. These aspects often result in 'functional requirements' (such as weight, pressure drop, noise, and stiffness). These requirements are often easier to formulate, measure, and verify compared to






Figure 7. Excerpt of a value creation strategy highlighting two alternative value drivers to respond to the need to possess "ability to quickly integrate" the FOGV, leading to two different design solutions.

attributes related to design or integration (assembly), which are typically of interest to internal stakeholders such as the FOGV manufacturer. These aspects, often related to 'non-functional' attributes of a design, are more difficult to formulate and assess. To address the need for the 'ability to quickly integrate the FOGV' in the

'integration' process, two VDs are identified: 'weld time' (impacting Solution A) and 'number of fittings/interfaces' (impacting Solution B). The reason for using VDs is to retain the benefits of requirements (such as measurability and clarity) while allowing multiple solutions to be explored. Formulating only a requirement for 'maximum allowable weld time' would imply Solution A (welding FOGV vanes to the outer structure). However, an alternative requirement – 'number of fittings/ interfaces' – leads to another solution (pipe fittings on machined holes – Solution B). A more general requirement, such as 'maximum allowable assembly time,' could potentially cover both solutions, but it would lack the specificity needed for unbiased and measurable verification, a key systems engineering principle (INCOSE 2023). It also limits the potential for parametric computational design studies, thereby restricting design exploration capabilities.

Another focal point of Figure 7 is to emphasize another key advantage of VDs: their ability to influence multiple needs. For instance, integrating vanes with fittings supports 'frequent upgradability' since vanes can be disassembled and reassembled, unlike welding. This demonstrates how VDs help keep the requirement space as solution-independent as possible, particularly for complex attributes that require iteration and reformulation throughout the development process.

4.3. Define solution design space

By moving to the 'design' tab, users can start to define their designs (Figure 8) by importing an Excel file that contains the numerical or categorical values for the designs under study, according to the VDs specified in the VCS. The calculation of these VDs comes from dedicated software tools or assessment methods, which are used to populate the Excel file. Figure 8 shows the simulation or assessment methods used to compute four VDs:

- 1. Design similarity to previous products, calculated using the method proposed in Bonde *et al.* (2023), which impacts the need to reduce risk during development;
- Socioenvironmental material criticality score, based on Hallstedt & Isaksson (2017), which impacts the need to promote environmental sustainability in manufacturing;
- 3. Stiffness, calculated using structural simulation tools using a design automation framework (more details provided in Andersson *et al.* 2023); and
- 4. Pressure drop, a key aerodynamic feature, calculated using an aerodynamic software developed internally by the company.

To provide more flexibility and accommodate the different stages of the design process (characterized by varying levels of design maturity), input can also be provided by manually generating designs in the 'design view.' Additionally, the tool allows for the creation of more radical designs beyond those defined by parametrically varying the VDs. For example, the choice of using a rotating structure instead of a static FOGV would change the nature of the VDs – for instance, this 'rotating FOGV' could generate electricity, and the generated power could become a novel VD.

4.4. Perform value and cost studies

The last step is to evaluate the designs against the VCSs. Traditionally, this evaluation is conducted using QFD-like approaches that require experts to assign semi-




Figure 8. Import design input data, from an excel file taking input from simulation tools.

quantitative scores to the relationships between needs and VDs (e.g., Bertoni *et al.* 2018). In the case of a large design space, such as the one in this FOGV case study (where 90 designs generated with design automation techniques described in Figure 8 are evaluated against 5 VCSs), this expert evaluation can be rather tedious (i.e., there would be 450 potential QFDs to be filled). For these reasons, the VD-MBSE method has implemented a more monetary and simulation-based evaluation of design alternatives, using the SV model (Collopy & Hollingsworth 2011).

This monetary evaluation is made possible through the link between the ISO 15288 processes and the value creation strategies. Since each process is connected to VDs (Figure 7) – which are the elements that vary among design alternatives – it becomes possible to associate each design with the time, cost, and potential revenue it incurs in each process by adopting a discrete-event simulation (DES) algorithm (Browning & Eppinger 2002). Figure 9 shows the overall logic of the DES algorithm, which enables the calculation of the SV for each design alternative based on its characteristics (the VDs).

The simulation of time, cost, and revenue for each product with a specific design configuration "flowing through" the processes allows for the calculation of SV. This first requires organizing the order of the processes. This input can be provided in the 'process hierarchy' tab (Figure 9) in the form of a design structure matrix (DSM), as shown in Browning & Eppinger (2002). Although the sequence of processes can be visualized as a process flow (as shown in the upper part of Figure 9), the DSM format is chosen for its compactness. Figure 9, five processes are




Figure 9. Overall architecture of the DES algorithm and SV model.

selected: architectural design, implementation/fabrication, integration, operation, and maintenance.

The DES algorithm requires that 'entities' (in this case, new FOGVs with a specific design configuration) are 'injected' into the business at a specified rate. Since some processes are independent of the number of entities (e.g., the design process is done only once), it is possible to specify which processes should be run a single time. For the other processes, entities flow at a defined rate (e.g., 1,000 FOGVs per year).

As entities enter a process, the time, cost, and revenue are calculated and accumulated from previous processes. Afterwards, the entities move to the next process based on the defined hierarchy. The time, cost, and revenue spent in each process are functions of two variables:

- 1. the value drivers, which vary for each design (Figure 8), and
- 2. design-independent factors (e.g., aircraft range and energy price), which are defined as *external factors*, since they are outside the control of the engineers.

These relationships are set in the 'connect design to VCS' tab (Figure 10) using a formula editor.

The figure shows the equation for the operation cost (with formulas based on Hepperle 2012). The equation editor allows users to manipulate classical Excel operators, such as 'if' statements and Boolean operators for categorical variables. Figure 10 illustrates how the editor visualizes all the VDs defined in the VCS for that specific process (e.g., mass and pressure drop), making them selectable for the formula (highlighted in red for easier identification). The external factors are shown in blue and are defined in the 'external factors' tab (Figure 11). Since external factors depend on the business context, they are closely linked to the




Figure 10. Editor for the operation cost formula, highlighting the connection between the VDs (e.g., mass and pressure drop, shown in red) and the external factors (e.g., aircraft range and energy price, shown in blue).




Figure 11. External factors tab.

defined VCS. For example, an ultra-short flight has a different range than a medium or ultra-long flight. For this reason, the tab displays the selected VCS by default, allowing users to define appropriate values for the external factors.

The definition of these relationships is the most data-intensive and assumption-intensive part of the method, as it requires the quantification in monetary terms of VDs that are not strictly related to the functionality of the product. For example, in Figure 9, a super-linear relationship has been defined between the design similarity of the new product and the design cost (i.e., a new radical design will result in a super-linear increase in design cost). While this paper acknowledges the limitations of such assumptions on the final SV results, the main focus is to provide support for making it easier to change and update these relationships (as MBSE tools typically aim to do), while leaving the correctness of the input data to the user. However, the paper also recognizes the importance of handling uncertainties, and future research directions on this topic are presented in the discussion.

Once all the equations have been defined, it is possible to run the DES algorithm for all selected designs across all selected VCSs. Since the DES algorithm operates in step changes (Browning & Eppinger 2002), the algorithm interpolates the results of the step changes to make a more intuitive visualization (lower part of Figure 9). Additionally, the monetary results are time-adjusted using a discount rate, as is commonly done in economic analysis. All simulations are automatically saved for further inspection. The results of the SV curves (i.e., the cost and revenue profile for each design-VCS combination) can be directly inspected in the web interface or exported as an Excel file for further post-processing.

Output from the method: sets of compatible designs for evolving business contexts

This section describes how the results from the modelling tool can be used. In situations where it is not yet clear which business strategies (articulated as VCSs) will take off in the future – such as in the electrification of aerospace propulsion – the objective is not to find the 'best' design alternatives (i.e., those with the highest SV), but rather to identify the designs that are most valuable across the widest set of VCSs. Figure 12 shows an example to illustrate this difference.

Each of the two tables shows an excerpt from the simulation results for the 90 designs evaluated against the 5 VCSs (resulting in a total dataset of 450 entries). The tables display 3 out of the 23 VDs that compose the dataset. One of the three VDs is connected to a functional attribute (mass), while the other two relate to nonfunctional attributes: the ability to double source, and the design similarity to previous products (calculated using the method proposed in Ref. 1 – omitted to preserve double-blind review). The upper part of Figure 12 shows 10 designs filtered from the dataset by selecting those with the highest SV. The figure highlights that each of these designs is optimized for a single VCS, and only two VCSs show the highest SV. This indicates that while these designs may be optimal, they are highly dependent on the assumption that the corresponding VCS will be implemented. There is a significant risk that these designs will be suboptimal if other VCSs (e.g., VCS3 – disruptive 'Aeronautic SpaceX' customer, or VCS4 – long-lasting circular solution) emerge as dominant. Furthermore, SV results rely

on both economic and technical assumptions, which may change and alter the design rankings.

A different strategy is shown in the lower part of Figure 12. Each line in the plot represents one of the 90 designs simulated across the five value creation strategies (VCSs). This new filter identifies another set of 10 designs, with Design Case 52 being notable for presenting comparable SV across three VCSs (VCS1, VCS2,

a) Filter by max Surplus Value

	Value Drivers					
Designs	Design similarity [0- 1]	Ability to double source [YES/NO]	Mass [kg]	Value Creation Strategy	Surplus Value (kEuro)	Compatible with other VCS?
Design Case 17	0.15	YES	109	VCS2	5239	NO
Design Case 65	0.21	YES	112	VCS2	5222	NO
Design Case 12	0.15	YES	105	VCS2	5204	NO
Design Case 34	0.13	NO	110	VCS2	5108	NO
Design Case 7	0.00	NO	107	VCS2	5107	NO
Design Case 55	0.16	YES	105	VCS2	5089	NO
Design Case 85	0.20	YES	112	VCS2	5065	NO
Design Case 27	0.28	YES	145	VCS2	5063	NO
Design Case 91	0.27	NO	110	VCS2	5050	NO
Design Case 44	0.08	YES	113	VCS1	5049	NO

b) Filter by VCS compatibility

	Value Drivers					
Designs	Design similarity [0-	Ability to double source [YES/NO]	Mass [kg]	Value Creation Strategy	Surplus Value (kEuro)	Compatible with other VCSs?
Design Case 53	0.37	YES	134	VCS1	3834	NO
Design Case 52	0.13	YES	136	VCS1	3654	3
Design Case 41	0.16	NO	105	VCS2	3825	NO
Design Case 23	0.38	NO	143	VCS2	3789	NO
Design Case 52	0.13	YES	136	VCS2	3639	3
Design Case 35	0.16	NO	109	VCS3	3827	2
Design Case 68	0.21	YES	112	VCS4	3695	NO
Design Case 52	0.13	YES	136	VCS4	3645	3
Design Case 88	0.19	YES	110	VCS4	3639	NO
Design Case 35	0.16	NO	109	VCS4	3607	2

Figure 12. Examples of filtered results for 10 of the 90 FOGV design alternatives against 5 VCSs. In the upper part, the results are filtered by selecting the 10 designs with the highest SV; however, each design is optimized for a single individual VCS. In the lower part, the filter is applied to select designs with slightly lower SV, but which present comparable SV across multiple VCSs.

and VCS4). This approach – favouring compatibility over optimization – is promoted in set-based concurrent engineering methodologies (Sobek *et al.* 1999) and is particularly relevant in situations where business contexts (articulated through the VCSs) may change. By filtering the results and further examining the VDs, engineering teams can explore why certain designs are more compatible and potentially combine features (e.g., a hybrid configuration with vanes both welded and assembled using fittings) to create new design alternatives. The filtering process also reveals that all designs compatible with VCS5 (mediumrange flight, 1400 km) have low SV. This suggests that full electrification of aerospace products may not be viable for medium-range flights unless combined with hybrid configurations (e.g., hydrogen or fuel cells).

Positioning the proposed method onto MBSE: a quantitative study

This section has the objective to analyse the advantages of VD-MBSE compared to other traditional MBSE approaches and document-based SE practices. Since the analysis is based on a number of assumptions derived from the literature (e.g., Carroll & Malins 2016), any comparison is subject to uncertainty. Therefore, the following analysis should be considered a quantitative 'positioning study' rather than a direct comparison.

The first step of this study was to apply the proposed method at a meta-level on the method itself, by creating a VCS. This is shown in Figure 13.

The proposed method targets two phases of a project lifecycle: the business and mission analysis, and the requirements analysis process. The main needs it fulfills are:

- 1. the ability to analyze the impact of multiple missions to reduce the risk of rework due to changes in the business context, and
- the ability to quickly iterate value aspects to reduce the risk of rework caused by the volatility of requirements during the development process—a problem discussed in Peña & Valerdi (2015).

		Stakeholder			
Process	Stakeholder	Expectations	Stakeholder Needs	Rank Weight	Value Drivers
Business or	Value Analysis	Reduce rework	Ability to analyze the	12%	Number of analyzed
mission	Team	due to change in	impact of multiple	12/0	missions [#]
analysis		targeted business	missions simultaneously		
		contexts			
Requirements	Value Analysis	Reduce rework	Ability to quickly iterate	8%	Number of aspects
analysis	Team	due to volatility	functional aspects	070	related to functional
		of requirements			aspects [#]
		in the			Number of designs
		development			imported [#]
		process	Ability to quickly iterate	80%	Number of value
			non-functional aspects	3070	drivers related to non-
					functional aspects [#]
					Number of designs
					imported [#]

Figure 13. VCS applied on the proposed method, highlight the main needs it addresses.

Table 1. Input data for positioning study, with the 23 VDs managed during the case study and assumed effort if no MBSE technique is used

Coeff	Process	Number of value drivers related to FRs	Number of value drivers related to NFRs	SE effort on FRs (with no MBSE)	SE effort on NFRs (with no MBSE)
1	Business or mission analysis	0	0	0.0	0.0
2	Requirements analysis	0	0	0.0	0.0
3	Architectural design	0	1	0.0	1.0
4	Part Acquisition (Implementation)	0	3	0.0	4.0
5	Machining (Implementation)	0	4	0.0	6.7
6	Integration	0	4	0.0	8.0
7	Transition	1	0	0.8	0.0
8	Operation	5	2	4.4	5.3
9	Maintenance	2	1	2.0	3.0
	TOTAL	8	15	7.2	28

The next step is to perform a rank-weight indicating the priority given to the needs. A stronger emphasis is placed on non-functional aspects, since the modeling of functional aspects is assumed to be already addressed in traditional MBSE methods, as detailed in the following sections.

The input data for the analysis consists of the 23 VDs examined in the present study, and the lifecycle process each VD is related to. The authors then proceeded to classify each VD by type – whether it is related to a functional or non-functional aspect. These results are presented in Table 1.

The study highlighted 8 VDs related to functional requirements (FRs), while 15 are related to non-functional requirements (NFRs). These proportions are consistent with recent studies conducted by Morkos $et\,al.$ (2019) on student teams. To calculate the effort spent on each VD if no model-based technique is used, a simple assumption was applied using a coefficient that weights the effort depending on the phase in which a specific VD is discovered and managed (i.e., VDs discovered and managed in later phases will require more effort). Additionally, since FRs are typically easier to measure and articulate (Morkos $et\,al.$ 2019), an effort weight of 1/9 was assigned to FRs, while managing NFRs was assigned a weight of 3/9. For example, the maintenance process (coefficient 9, as it is the latest phase) has 2 FRs and 1 NFR. Managing the 2 FRs during the maintenance phase would imply an effort of $2 \times 9 \times (1/9) = 2$, while managing the NFR would imply an effort of $1 \times 9 \times (3/9) = 3$.

Based on this input data, the benefit of an MBSE and VD-MBSE approach was estimated, and the results are provided in Figure 14. The graph shows the cumulative effort required to manage both FR (blue bars) and NFR requirements (red bars) over the course of a project – assuming no model-based approach is used. Regarding FR requirements (which account for 20.5% of the total effort), the assumption is that MBSE tools already provide mechanisms to support their





Figure 14. Estimated investments and savings in terms of effort for a VD-MBSE approach.

formulation, measurement, and traceability (therefore the VD-MBSE has no benefit regarding the strict management of FRs). It was therefore assumed that using MBSE to work on the 8 FR requirements during the requirements analysis stage (green bar) for 5.1% of the time would save 20% of managing these FRs in the later stages. These proportions appear to align with studies on the economic benefits of MBSE (Madni & Purohit 2019).

Instead, the VD-MBSE approach was estimated to have the benefit of reducing the risk associated with managing NFRs, which account for 79.5% of the total effort. Therefore, working with the 15 NFRs during the requirements analysis stage would save this 79.5%. As shown in Figure 14, applying VD-MBSE to manage the 15 NFRs would require some initial investment effort, estimated at 32.2% of the time.

An additional benefit of VD-MBSE is its ability to analyze multiple business contexts simultaneously, which helps reduce the risk of needing to change the design architecture if the targeted context shifts, as demonstrated in Figure 12. Traditionally, MBSE tools offer limited support for handling multiple missions or business scenarios, thereby restricting their effectiveness during the business or mission analysis phases (Madni & Purohit 2019). Figure 15 illustrates an example of this limitation in Capella, a commonly used MBSE software.

a) Mission Capabilities Diagram



b) Logical Architecture Diagram




Figure 15. Capella used for the business and architectural design phases as (a) mission capabilities diagram and (b) logical architecture diagram.

Capella includes 'mission' and 'capabilities' objects, which correspond to the value creation strategies and the needs in VD-MBSE (as implemented in the Club Design software). In Capella, each of these missions can be connected to the 'logical architecture,' which contains the requirements for each system component in each mission (Figure 15). The challenge is that each mission may require a very different logical architecture and set of requirements. For example, in the case study, 90 designs were analysed across 5 missions, resulting in a total of 450 logical architecture diagrams that would need to be created.

Instead, using Club Design before transitioning to MBSE environments helps identify which missions are compatible and which are non-valuable (e.g., VCS5 – 'Medium range flight'). This allows for the definition of only the compatible architectures and the corresponding requirement ranges, significantly reducing the modelling effort. In Figure 14, this benefit was quantified by considering the effort spent on modelling four additional businesses or missions in VD-MBSE, accounting for 3.8% of the time. This investment would save the time required in MBSE to create four mission capability diagrams and logical architectures during the architectural design phases—thereby saving 11.4%.

7. Discussion

While qualitative support for requirements elicitation has been implemented in industry (e.g., Laporti, Borges & Braganholo 2009; Azadegan, Papamichail & Sampaio 2013; Fortineau, Paviot & Lamouri 2019), such approaches are often based on document-based methods that limit the ability to maintain consistency when changes occur – something that is frequently inevitable in the early stages of product development. For these reasons, MBSE has been proposed to improve consistency and traceability in the face of iterations during system development (Hehenberger *et al.* 2016; Huldt & Stenius 2019). However, the modeling process is often considered tedious and cumbersome in the architecting phases of product development, which are characterized by uncertainties related to the markets and the product. In this context, the proposed VD-MBSE method (prototyped and demonstrated in the tool Club Design) serves as a flexible tool to work with 'value drivers' and preliminary requirements, enabling the assessment of a larger number of designs before committing to the development of detailed MBSE models for managing and tracing requirements tied to a single solution. For this reason, the method can be used not only by engineering teams exploring design solutions but also by marketing groups, who interact both externally with customers and internally with the engineering team. This was particularly relevant in the case study, where the aerospace component manufacturer is not responsible for the entire engine but is heavily investing in whole-engine models to better understand the boundaries of the structural components it supplies to the engine OEM. Therefore, the tool can be used to facilitate communication both externally (with aircraft and engine OEMs) and internally within the organization, improving collaboration between marketing and design teams.

This paper emphasizes the monetary evaluation of designs, including the quantification of critical dimensions (e.g., environmental impact, social considerations) that may influence decision-making. While there is a broad body of literature on sustainability evaluation metrics that adopt a broader perspective (e.g., Hallstedt 2017), this paper focused on monetary quantification to allow these

dimensions to emerge within the decision-making process, making them comparable to other aspects using a common, easily understandable format for decision-makers. For this reason, this paper included the quantification of environmental concerns as well (e.g., the socio-ecological material criticality score shown in Figure 8).

However, monetary quantification of such aspects presents several challenges, as it involves assumptions and uncertainties. Addressing these challenges was considered outside the scope of this paper, which instead focused on supporting the ability to easily change and update these relationships – consistent with the goals of MBSE – while leaving responsibility for the correctness of input data to the user. Nevertheless, this paper acknowledges that the field of monetary quantification for socio-environmental aspects is evolving, beginning with contingent valuation methods in the 1980s (Hanemann 1994) and continuing with more recent advances enabled by large language models and AI (Khuc & Tran 2023). Future work will focus on understanding the benefits of integrating such techniques into VD-MBSE.

Despite the value of the results, the method produces a substantial amount of quantitative information (e.g., design parameters and cost/revenue data), which may be sensitive in collaborative environments where partners operate in a 'coopetition' mode – such as the aircraft OEM and the engine component manufacturer in this study. This sensitivity may hinder the willingness to share information about the value of design alternatives. For this reason, the articulation of VCSs can also serve as a communication framework to share the value of design alternatives among OEMs and suppliers using only textual information and the 'adimensional' rank-weights described earlier in Section 4.1, thereby acting as an 'information protection shield' between partners. One possible strategy is to calculate the sensitivities between the VDs and SV, as performed by Soban & Mavris (2013). By aggregating these sensitivities 'backwards' onto each need, adimensional scores can be generated and used to update the VCS rank weights. This allows the VCSs alone to be shared among partners without disclosing specific details about the design alternatives or the underlying data used in SV calculations.

The method presented in this paper has been applied in the aerospace industry, with further investigations currently underway in the space and automotive sectors. These industries are typical users of MBSE approaches due to the complexity of their systems. However, the method also shows potential value for sectors that have traditionally benefited less from MBSE, such as home, lifestyle, fashion, and consumer packaged goods (Madni & Purohit 2019). The growing investment in circular economy solutions within these sectors (Stahel 2016) is expected to increase the need to manage higher levels of market and business complexity (e.g., managing multiple lifecycles embedded in a system-of-systems; Shaked & Reich 2019). Looking ahead, for systems situated within a circular economy scenario, there will be a significant development risk if the implications of multiple market scenarios on system alternatives are not explored with a high degree of granularity.

8. Conclusion

The proposed method and the associated software tool extend traditional MBSE by addressing its limitations in early-stage conceptual design, particularly in industries with evolving and uncertain markets. By integrating value modeling and

simulation capabilities with ISO standards, the method allows for the concurrent exploration of business and system alternatives. This enables flexible decision-making and design iteration while maintaining traceability. The electrification of aerospace products case study demonstrated the method's ability to facilitate collaboration between OEMs and suppliers, supporting value-based trade-offs without compromising sensitive information. Its applicability extends beyond aerospace, offering potential in sectors such as space, automotive, and consumer goods – particularly in managing market complexities. Further research is needed to refine the method's use in other industries and to improve data-sharing practices. Overall, the method complements MBSE by adding flexibility and early-stage exploration, making it a valuable tool for industries facing complex design challenges.

Acknowledgements

This research has received funding from the European Union's Horizon 2020 research and innovation programme (CHEOPS LP project) under grant agreement No 101004331, and from the ITEA 3 via the Swedish Innovation Agency VINNOVA within the 19009 DEFAINE (Design Exploration Framework based on AI for froNt-loaded Engineering) project.

References

- Andersson, P., Lejon, M., Chidambaranathan, S., Wejletorp, S. D., Panarotto, M. & Jacobson, M. 2023 Multidisciplinary design space exploration: an electric fan thruster component design use case. Paper presented at EUCASS-CEAS 2023 Technical Sessions.
- **Azadegan, A., Papamichail, K. N. & Sampaio, P.** 2013 Applying collaborative process design to user requirements elicitation: a case study. *Computers in Industry* **64** (7), 798–812.
- Bertoni, M., Bertoni, A. & Isaksson, O. 2018 Evoke: a value-driven concept selection method for early system design. *Journal of Systems Science and Systems Engineering* 27, 46–77.
- Bonde, J. M., Kokkolaras, M., Andersson, P., Panarotto, M. & Isaksson, O. 2023 A similarity-assisted multi-fidelity approach to conceptual design space exploration. *Computers in Industry* 151, 103957.
- Browning, T. R. & Eppinger, S. D. 2002 Modeling impacts of process architecture on cost and schedule risk in product development. *IEEE Transactions on Engineering Man*agement 49 (4), 428–442.
- Carroll, E. R. & Malins, R. J. 2016 Systematic Literature Review: How is Model-Based Systems Engineering Justified? Sandia National Laboratories
- Collopy, P. D. & Hollingsworth, P. M. 2011 Value-driven design. *Journal of Aircraft* 48 (3), 749–759.
- Donelli, G., Boggero, L. & Nagel, B. 2023 Concurrent value-driven decision-making process for the aircraft, supply chain and manufacturing systems design. Systems 11 (12), 578.
- **Dori, D.** 2024 Model-based standards authoring: ISO 15288 as a case in point. *Systems Engineering* **27** (2), 302–314.

- Fantoni, G., Coli, E., Chiarello, F., Apreda, R., Dell'Orletta, F. & Pratelli, G. 2021 Text mining tool for translating terms of contract into technical specifications: development and application in the railway sector. *Computers in Industry* **124**, 103357.
- **Fortineau, V., Paviot, T. & Lamouri, S.** 2019 Automated business rules and requirements to enrich product-centric information. *Computers in Industry* **104**, 22–33.
- Hallstedt, S. I. 2017 Sustainability criteria and sustainability compliance index for decision support in product development. *Journal of Cleaner Production* 140, 251–266.
- **Hallstedt, S. I.** & **Isaksson, O.** 2017 Material criticality assessment in early phases of sustainable product development. *Journal of Cleaner Production* **161**, 40–52.
- **Hanemann, W. M.** 1994 Valuing the environment through contingent valuation. *Journal of Economic Perspectives* 8 (4), 19–43.
- Hehenberger, P., Vogel-Heuser, B., Bradley, D., Eynard, B., Tomiyama, T. & Achiche, S. 2016 Design, modelling, simulation and integration of cyber physical systems: methods and applications. *Computers in Industry* **82**, 273–289.
- **Hepperle, M.** 2012 Electric flight-potential and limitations. AVT-209 Workshop, Lisbon, 22–24 October 2012.
- **Honour, E.** 2010, July 11.4. 2 systems engineering return on investment. In *INCOSE International Symposium*, Vol. **20**, No. 1, pp. 1422–1439. INCOSE.
- Huldt, T. & Stenius, I. 2019 State-of-practice survey of model-based systems engineering. Systems Engineering 22 (2), 134–145.
- INCOSE 2023 INCOSE Systems Engineering Handbook. John Wiley & Sons.
- International Organization for Standardization 2023a ISO/IEC/IEEE FDIS 15288:2023 -Systems and software engineering — System life cycle processes, Geneva, Switzerland.
- International Organization for Standardization 2023b ISO/IEC/IEEE 24641:2023 Systems and Software engineering Methods and tools for model-based systems and software engineering, Geneva, Switzerland.
- Isaksson, O., Kossmann, M., Bertoni, M., Eres, H., Monceaux, A., Bertoni, A., Wiseall, S. & Zhang, X. 2013, June Value-driven design—a methodology to link expectations to technical requirements in the extended enterprise. In *INCOSE International Symposium*, Vol. 23, No. 1, pp. 803–819. INCOSE.
- Khuc, V. Q. & Tran, D. T. 2023 Contingent valuation machine learning (CVML): a novel method for estimating citizens' willingness to pay for a safer and cleaner environment. *Urban Science* 7 (3), 84.
- Laporti, V., Borges, M. R. & Braganholo, V. 2009 Athena: a collaborative approach to requirements elicitation. *Computers in Industry* 60 (6), 367–380.
- Lavi, E. & Reich, Y. 2024 Cross-disciplinary system value overview towards value-oriented design. Research in Engineering Design 35 (1), 1–20.
- **Madni, A. M. & Purohit, S.** 2019 Economic analysis of model-based systems engineering. *Systems* 7 (1), 12.
- Martin, J. N. 1998 Overview of the EIA 632 standard: processes for engineering a system. In 17th DASC. AIAA/IEEE/SAE. Digital Avionics Systems Conference. Proceedings (Cat. No.98CH36267), Bellevue, WA, USA, pp. B32–1. IEEE. doi:10.1109/DASC.1998.741462.
- Morkos, B., Joshi, S. & Summers, J. D. 2019 Investigating the impact of requirements elicitation and evolution on course performance in a pre-capstone design course. *Journal of Engineering Design* 30 (4–5), 155–179.
- Panarotto, M., Borgue, O. & Isaksson, O. 2020a Modelling flexibility and qualification ability to assess electric propulsion architectures for satellite megaconstellations. *Aero-space* 7 (12), 176.

- Peciak, M. & Skarka, W. 2022 Assessment of the potential of electric propulsion for general aviation using model-based system engineering (MBSE) methodology. *Aerospace* 9 (2), 74.
- **Peña, M.** & **Valerdi, R.** 2015 Characterizing the impact of requirements volatility on systems engineering effort. *Systems Engineering* **18** (1), 59–70.
- Pohya, A. A., Wehrspohn, J., Meissner, R. & Wicke, K. 2021 A modular framework for the life cycle based evaluation of aircraft technologies, maintenance strategies, and operational decision making using discrete event simulation. *Aerospace* 8 (7), 187.
- Ramm, J., Pohya, A. A., Wicke, K. & Wende, G. 2024 Uncertainty quantification in hydrogen tank exchange: estimating maintenance costs for new aircraft concepts. *International Journal of Hydrogen Energy* 68, 159–169.
- **Shaked, A.** & **Reich, Y.** 2019 Designing development processes related to systems using a modeling framework. *Systems Engineering* **22** (6), 561–575.
- **Soban, D. S.** & **Mavris, D. N.** 2013 Assessing the impact of technology on aircraft systems using technology impact forecasting. *Journal of Aircraft* **50** (5), 1380–1393.
- **Sobek II, D. K., Ward, A. C. & Liker, J. K.** 1999. *Toyota's Principles of Set-based Concurrent Engineering.* MIT Sloan Management Review.
- Stahel, W. R. 2016 The circular economy. Nature 531 (7595), 435-438.
- **Wymore, A. W.** 1993 *Model-Based Systems Engineering*, 1st Edn. CRC Press. doi: 10.1201/9780203746936.
- Yang, L., Cormican, K. & Yu, M. 2019 Ontology-based systems engineering: a state-of-theart review. *Computers in Industry* 111, 148–171.